

UNDERCARRIAGE
MAIN UNDERCARRIAGE - PORT

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqp't. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
-	-	UNDERCARRIAGE, MAIN, PORT ASSEMBLY (EB8.40.1) Spares for:						-	-	-	-
-	-	LEG, Oleo, and Dunlop Wheel, Port Assembly (EB8.40.3) Spares for:						-	-	-	-
27G/4618243	Dunlop AH9780	BRAKE, UNIT (For spares see SP4515C, Vol 3 Pt 1 Section 2)						1	-	A	Q.1
13251	EB8.20.23	FAIRING, Fixed Group (Supplied with trim allowance) Spares for:						1	-	A	Q.1,2
17735	EA6.73.277	BRACKET, bottom Attachment of bottom bracket to fixed fairing						1	DTD610	C	Q.2
28D/9133012	A25/3C	Bolt, 2BA						2	-	C	Q.2
5970	EA6.73.93	Washer						2	-	C	Q.2
1413	EA1.20.6817	PANEL, Access, Group Spares for:						1	-	B	Q.2
28FP/4062619	Oddie 217/2	STUD						2	-	C	Q.2
28FP/1004893	Oddie 214	WASHER						2	-	C	Q.2
13858	EB8.20.4857	PANEL, access Attachment of access panel to fixed fairing						1	L72	C	Q.2
6217	EEAS1/1E	Screw, 1/4 in. BSF						15	S96	C	Q.2
21164	EA3.20.2869	PANEL, Hinged, Group Spares for:						1	-	B	Q.1
-	EA1.20.1679	HINGE (Make from Ref 28N/10363)						1	-	LM	Q.1
3025	EA1.20.1675	PANEL, hinge (16 swg)						1	DTD610	C	Q.1
520	EA1.40.435	SPRING						2	Spring Steel	C	Q.1
-	EA3.20.1627	SEAL, rubber 90 in. long (make from Ref. 4432) Attachment of fixed fairing to oleo leg						1	-	LM	Q.2
4174	EA1.40.519	Bolt, 5/16 in. BSF						8	-	C	Q.1
28W/1086617	AGS162/E	Washer, spring						8	-	C	Q.1,3
5796	EA6.40.7	LEG, Sliding and Oleo Head Group (Pre Mod 3211)						1	-	A	Q.1,3
32314	EA9.40.23	LEG, Sliding and Oleo Head Group (Mod 3211 Pre Mod 4270)						1	-	A	Q.1,3
34712	EA9.40.59	LEG, Sliding and Oleo Head Group (Mod 4270) Spares for:-						1	-	A	Q.1,3
-	-	HEAD, Oleo Assembly (EA6.40.3) (Pre Mod 4270)						-	-	-	Q.3
-	-	HEAD, Oleo Assembly (EA9.40.57) (Mod 4270) Spares for:-						-	-	-	Q.3
RESTRICTED											

RESTRICTED

UNDERCARRIAGE
MAIN UNDERCARRIAGE--PORT

Ref. No	Part No.							Description	No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6					
663	EA1.40.89							BALL, side stay joint Attachment of ball to Oleo Head	1	S11	C	Q.3
664	EA1.40.101							Bush, bearing	1	DTD412	C	Q.3
674	EA1.40.95							Ring, retaining	1	DTD124	C	Q.3
676	EA1.40.97							Ring, retaining	1	DTD124	C	Q.3
680	EA1.40.99							Stud	12	S11	C	Q.3
665	EA1.40.109							BUSH, pivot	2	DTD412	C	Q.3
666	EA1.40.111							BUSH, torque link lug Attachment of torque link bush to Oleo Head	2	DTD112	C	Q.3
673	EA1.40.679							Plug	2	L40	C	Q.3
21495	EA1.40.19							FORGING, Oleo Head (Pre Mod 4270)	1	-	C	
42058	EA9.40.55							FORGING, Oleo Head (Mod 4270)	1	-	C	
28N/9156370	SP21							NIPPLE, grease	2	-	C	Q.3
20656	EA1.40.127							PIPE, stack, group	1	-	C	Q.3
-	-							PISTON, Assembly (EA6.40.5) Spares for:-	-	-	-	Q.3
670	EA1.40.647							PISTON Attachment of piston to strut	1	DTD197	C	Q.3
1099	EEAS37/22A							Nipple, long	2	S11	C	Q.3
-	EEAS38/3A							Spoke, 2BA (make from Ref. 28R/6328)	1	S11	IM	Q.3
22528	EA6.40.33							PLATE, orifice Attachment of orifice plate to piston	1	S96	C	Q.3
683	EA1.40.61							Bolt, 2BA	3	S11	C	Q.3
672	EA1.40.651							RING, piston	1	BESA4K6	C	Q.3
28Y/9701165	AGS2096							VALVE, charging, hydraulic Attachment of charging valve to Oleo Head	1	-	B	Q.3
28D/1215078	AS1246/5C							Bolt, 2BA	1	-	C	Q.3
-	-							Chain, light brass, 4in. long	1	-	IM	-
669	EA1.40.103							Hook, "S" shaped	1	M.S.Wire	C	Q.3
28P/9486478	SP90/C5							Pin, split, 1/16 in. dia	1	-	C	Q.3
681	EA1.40.105							Tube, distance	1	L40	C	Q.3
28F/8014021	AGS1138/B							Washer	1	-	C	Q.3
682	EA1.40.149							Washer, locking	1	DTD214	C	Q.3
28W/9416643	SP47/C							Washer, spring. 2BA	1	-	C	Q.3

UNDERCARRIAGE
MAIN UNDERCARRIAGE - PORT

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqp. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
-	-						LEG, Sliding and Axle Assembly (EA3.40.7) (Pre Mod 3211)	-	-	-	Q.3
							LEG, Sliding and Axle Assembly (EA3.40.225) (Mod 3211)	-	-	-	Q.3
							Consisting of:-				
26640	EA3.40.201						BOLT, 2BA axle clamp	1	S95 or S96	C	Q.3
2467	EA3.40.45						BUSH, bearing, group	1	-	C	Q.3
684	EA1.40.161						BUSH, bearing	2	DTD412	C	Q.3
	EA3.40.217						CLAMP, Axle, Group	1	-	-	Q.3
							Consisting of:				
21355	EA3.40.23						BUSH	1	L40	C	Q.3
13024	EA3.40.183						CLAMP, axle	1	S96	C	Q.3
1753	EA3.40.19						LINK, towing	1	S96	C	Q.3
21537	EA3.40.21						WASHER, towing link	1	L40	C	Q.3
28M/1011476	A27/JS						NUT, slotted $\frac{3}{8}$ in. BSF	1	-	C	Q.3
28P/1040788	SP90/C8						PIN, split 1/16 in. dia.	1	-	C	Q.3
28W/9419466	SP13/J						WASHER, $\frac{3}{8}$ in.	1	-	C	Q.3
1462	EA3.40.9						LEG, sliding and axle, group	1	-	A	Q.3
691	EA1.40.41						NUT, stop	1	S11	C	Q.3
*692	EA1.40.653						PISTON, shock absorber (Pre Mod 3211)	1	DTD197	C	Q.3
37461	EA3.40.219						PISTON, shock absorber (Mod 3211)	1		C	Q.3
693	EA1.40.175						PLATE, orifice	1	S97	C	Q.3
694	EA1.40.655						PIUG, oleo base (Pre Mod 2760)	1	DTD683	C	Q.3
14701	EA3.40.203						PIUG, oleo base (Mod 2760)	1	DTD683	C	Q.3
695	EA1.40.677						PIUG, pivot bearing bush	2	L40	C	Q.3
14705	EA3.40.215						RING, backing (Mod 2760)	2	Fabric CX18	C	Q.3
12913	EA1.40.657						RING, distance	1	DTD683	C	Q.3
697	EA1.40.57						RING, piston	1	BESA 4K6	C	Q.3
12915	EA1.40.45						RING, retaining	1	S3	C	Q.3
696	EA1.40.37						RING, sealing rubber (Pre Mod 2760)	2	Shore Hardness 70	C	Q.3
698	EA1.40.661						RING, sealing rubber (Pre Mod 2760)	1	Shore Hardness 60	C	Q.3
14703	EA3.40.213						RING, sealing, rubber (Mod 2760)	2	S80	C	Q.3
14704	EA3.40.211						RING, sealing, rubber (Mod 2760)	1	S15	C	Q.3
14702	EA3.40.205						RING, sealing, rubber (Mod 2760)	1	S15	C	Q.3
21354	EA1.40.659						RING, stop, shock absorber	1	DTD683	C	Q.3
21221	EA1.40.635						RING, spacer (Pre Mod 2760)	2	DTD138	C	Q.3
699	EA1.40.165						SCREW, grub, piston locking (Pre Mod 3211)	1	S1	C	Q.3
32210	EA3.40.221						PIN, locking, piston (Mod 3211)	1	-	C	Q.3
700	EA1.40.167						SCREW, grub, stop nut locking	1	S1	C	Q.3
14706	EA3.40.209						SEAL, housing (Mod 2760)	1	L65	C	Q.3
14700	EA3.40.207						SPACER, (Mod 2760)	1	L1	C	Q.3
683	EA1.40.61						STUD, orifice place	6	S11	C	Q.3
701	EA1.40.39						WASHER, fibre	1	BS126	C	Q.3
702	EA1.40.43						WASHER, packing, 3/16 in. thick	1	Hard Felt	C	Q.3
NOTE: *	26PZ/692 EA1.40.653 still required 26PZ/37461 EA3.40.219 found unsuitable as a spare:										

RESTRICTED

UNDERCARRIAGE
MAIN UNDERCARRIAGE - PORT

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
3631	EA1.40.27						LINK, torque top Attachment of top torque link to oleo head	1	DTF683	C	Q.3
704	EA1.40.69						Pin, bearing	1	S11	C	Q.3
707	EA1.40.77						Screw, 1 in. BSF	1	S11	C	Q.3
708	EA1.40.139						Screw, locking, $\frac{1}{2}$ in. BSF	1	S1	C	Q.3
709	EA1.40.619						Shim	1	Lam.Alum.	C	Q.3
711	EA1.40.73						Sleeve	1	S11	C	Q.3
713	EA1.40.75						Washer, bearing	1	DTF412	C	Q.3
718	EA1.40.147						Washer, bearing	1	DTF412	C	Q.3
714	EA1.40.79						Washer, locking	1	DTF124	C	Q.3
3632	EA1.40.28						LINK, torque, bottom Attachment bottom torque link, to oleo sliding leg	1	DTF683	C	Q.3
703	EA1.40.67						Pin, bearing	1	S11	C	Q.3
707	EA1.40.77						Screw, 1 in. BSF	1	S11	C	Q.3
708	EA1.40.139						Screw, locking, $\frac{1}{2}$ in. BSF	1	S1	C	Q.3
709	EA1.40.619						Shim	1	Lam.Alum.	C	Q.3
710	EA1.40.71						Sleeve	1	S11	C	Q.3
713	EA1.40.75						Washer, bearing	1	DTF412	C	Q.3
718	EA1.40.147						Washer, bearing	1	DTF412	C	Q.3
714	EA1.40.79						Washer, locking	1	DTF124	C	Q.3
							Attachment of top and bottom torque links				
661	EA1.40.153						Bush, bearing	1	DTF412	C	Q.3
28N/9156370	SP21						Nipple grease	1	-	C	Q.3
28M/4095931	A27/SS						Nut, slotted, $\frac{3}{4}$ in. BSF	1	-	C	Q.3
1500	EA3.40.27						Pin, bearing	1	S97	C	Q.3
28P/221916	SP90/G14						Pin, split, $\frac{1}{2}$ in. dia.	1	-	C	Q.3
715	EA1.40.83						Washer	1	S11	C	Q.3
1514	EA3.40.29						Washer	1	S96	C	Q.3
1515	EA3.40.31						Washer	1	S96	C	Q.3
28N/9156370	SP21						NIPPLE, grease	4	-	C	Q.3
712	EA1.40.137						TAB, locking Attachment of locking tab to oleo head	1	S3	C	Q.3
28S/1200034	A31/B16						Screw, 4BA	1	-	C	Q.3
28W/9416642	SP47/B						Washer Attachment of sliding leg and oleo head group to wheel and wheel brake unit	1	-	C	Q.3
2168	EA6.40.35						Bolt, $\frac{1}{2}$ in. BSF	10	S97	C	Q.1
28M/4095892	A27/MS						Nut, slotted, $\frac{1}{2}$ in. BSF	10	-	C	Q.1
28P/9525532	SP90/E10						Pin, split, $\frac{1}{32}$ in. dia.	10	-	C	Q.1
2169	EA3.40.43						Washer, $\frac{1}{2}$ in.	10	DTF124A	C	Q.1

UNDERCARRIAGE

MAIN UNDERCARRIAGE - PORT

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
13859	EB8.40.21						LEVER, Cowl Door Mechanism, Group Spares for:	1	-	B	Q.1,2
13860	EB8.40.25						HINGE, group Attachment of hinge to cowl door mechanism lever	1	-	C	Q.2
28M/1278190	AGS2001/C1						Nut, stiff 2BA	1	-	C	Q.2
13861	EB8.40.33						Pin, hinge	1	S95	C	Q.2
28W/9419475	SP15/C						Washer, 2BA Attachment of cowl door mechanism lever to oleo leg group	1	-	C	Q.2
30827	EB8.40.113						Bolt, 1/4 in. BSF	4	-	C	Q.2
27G/2485	Dunlop AHM.2572						PIPE, feed for maxaret unit	1	-	C	Q.1
27G/2486	Dunlop AHM2574						PIPE, feed for maxaret unit	1	-	C	Q.1
27A/1450834	Dunlop DT.1609						TUBE, 43 in. x 12.5 in. x 21 in. (Mod 4386)	1	-	A	Q.1
27A/4655	Dunlop DR.1623 or Good Year GA.1266 or Firestone ZA.303						TYRE, 43 in. x 12.5 in. x 21 in.	1	-	A	Q.1
27G/2382	Dunlop AC11516						Unit, maxaret, automatic brake control (For spares see AP4515C, Vol 3 Pt 1 Section 2)	1	-	A	Q.1
27A/1450713	Dunlop AH52692						WHEEL, undercarriage (Mod 4386)	1	-	A	Q.1
34172	EA9.40.43						STAY, Side Undercarriage, Port Group (Mod 3585 Pre Mod 5051)	1	-	A	Q.1,2
6119299	EA9.40.73						STAY, Side, Undercarriage, Port Group (Mod 5051) Spares for:	1	-	A	Q.1,2
529	EA1.40.239						BOLT, stop 11/16 in. BSF Attachment of stop bolt to link stay bracket	1	S97	C	Q.2
537	EA1.40.353						Nut, 11/16 in. BSF	1	S11	C	Q.2

RESTRICTED

UNDERCARRIAGE

Canberra PR.Mk.9

MAIN UNDERCARRIAGE-PART

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
530	E.A1.40.405						BOLT, $\frac{5}{16}$ in. BSF Attachment of bolt to sequence valve operating bracket	1	S96	C	Q.2
28M/1011470	A27/GT						Locknut, $\frac{5}{16}$ in. BSF	1	-	C	Q.2
7112	E.A1.40.229						BRACKET, solenoid operating stud Attachment of stud bracket to side stay	1	S96	C	Q.2
28D/1011310	A25/8L						Bolt, $\frac{7}{16}$ in. BSF	2	-	C	Q.2
28D/1212690	A25/15L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28D/1212688	A25/18L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28M/9129449	A27/LS						Nut, slotted, $\frac{7}{16}$ in. BSF	4	-	C	Q.2
28F/9525532	SP90/E10						Pin, split, $\frac{3}{32}$ in. dia.	4	-	C	Q.2
7114	E.A1.40.403						BRACKET, sequence valve operating stud Attachment of stud bracket to side stay	1	L40	C	Q.2
28D/9133011	A25/2C						Bolt, 2BA	1	-	C	Q.2
28D/1212688	A25/18L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28W/1006940	1110						Lockwasher, "shakeproof"	1	-	C	Q.2
28M/9129449	A27/LS						Nut, slotted, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28F/9525532	SP90/E10						Pin, split, $\frac{3}{32}$ in. dia.	1	-	C	Q.2
531	E.A1.40.199						LEVER, Undercarriage Lock, Group Spares for:	1	-	B	Q.2
532	E.A1.40.213						BUSH	1	DTD197	C	Q.2
533	E.A1.40.200						LEVER, Undercarriage Lock, Group Spares for:	1	-	B	Q.2
532	E.A1.40.213						BUSH Attachment of undercarriage lock levers to side stay	1	DTD197	C	Q.2
525	E.A1.40.195						Bolt, $\frac{5}{8}$ in. BSF, hook catch pin	1	S65	C	Q.2
28N/9156370	SP21						Nipple, grease	1	-	C	Q.2
22176	E.A1.40.351						Nut, slotted, $\frac{5}{8}$ in. BSF	1	-	C	Q.2
28F/1221023	SP90/G12						Pin, split, $\frac{1}{8}$ in. dia.	1	-	C	Q.2
543	E.A1.40.219						Tube, distance	1	L40	C	Q.2
544	E.A1.40.291						Washer, tab	1	S3	C	Q.2
547	E.A1.40.417						Washer, under tab washer	1	DTD390	C	Q.2
28W/9419481	SP15/Q						Washer, $\frac{5}{8}$ in.	1	-	C	Q.2

UNDERCARRIAGE
MAIN UNDERCARRIAGE - PORT

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
13168	EA3.40.191						LEVER, Micro Switch Operating Group Spares for:	1	-	C	Q.2
179	EA1.40.569						SCREW, tappet Attachment of tappet screw to lever group	1	S11	C	Q.2
28M/1007403	A27/ET						Locknut, $\frac{1}{2}$ in. BSF Attachment of micro switch operating lever to side stay	1	-	C	Q.2
528	EA1.40.221						Bolt, $\frac{3}{8}$ in. BSF	1	S65	C	Q.2
28N/9156370	SP21						Nipple, grease	1	-	C	Q.2
26667	EA3.40.193						Nut, slotted, $\frac{3}{8}$ in. BSF	1	-	C	Q.2
542	EA1.40.217						Tube, distance	1	L40	C	Q.2
545	EA1.40.355						Washer	1	DTD390	C	Q.2
6472	EA1.40.225						LINK, Side Stay, Group Spares for:	1	-	B	Q.1,2
536	EA1.40.227						BUSH, bearing Attachment of link to side stay	2	DTD197	C	Q.2
526	EA1.40.197						Bolt, 1 in. BSF	1	S65 or 81	C	Q.2
28N/9156370	SP21						Nipple, grease	1	-	C	Q.2
12916	EA1.40.347						Nut, slotted, 1 in. BSF	1	-	C	Q.2
538	EA1.40.223						Plug, adaptor, for grease nipple	1	L40	C	Q.2
28P/1209392	SP90/K20						Pin, split, 3/16 in. dia,	1	-	C	Q.2
37307	EA1.40.765						Washer	1	-	C	Q.2
539	EA1.40.205						ROLLER, stop lever, group Attachment of roller to stop lever	1	-	C	Q.2
527	EA1.40.203						Bolt, $\frac{3}{8}$ in. BSF	1	S96	C	Q.2
40530	EA1.40.349						Nut, slotted $\frac{3}{8}$ in. BSF (make from 28M/13123)	1	-	LM	Q.2
28P/1040788	SP90/C8						Pin, split, 1/16 in. dia.	1	-	C	Q.2
7113	EA1.40.233						SLEEVE, operating spring for undercarriage uplock	1	L40	C	Q.2
540	EA1.40.237						SPRING, compression at lock stop	1	Spring Steel	C	Q.2
40650	EA9.40.39						STAY, side, port (Mod 3585 Pre Mod 5051)	1	-	B	-
6119308	EA9.40.79						STAY, side, port (Mod 5051)	1	-	B	-
541	EA1.40.235						STOP, undercarriage lock (For attachment Main Undercarriage to Wing. See Section HA)	1	S11	C	Q.2

RESTRICTED

UNDERCARRIAGE
MAIN UNDERCARRIAGE-STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
-	-	UNDERCARRIAGE, MAIN STARBOARD ASSEMBLY (EB8.40.2)						-	-	-	-
-	-	Spares for:-						-	-	-	-
-	-	LEG, Oleo and Dunlop Wheel Starboard Assembly (EB8.40.4)						-	-	-	-
-	-	Spares for:-						-	-	-	-
27G/4618244	Dunlop AH9781	BRAKE UNIT, (For spares see AP4515C, Vol.3, Pt.1 Section 2)						1	-	A	Q.1
13252	EB8.20.24	FAIRING, Fixed, Group (Supplied with trim allowance)						1	-	A	Q.1,2
17736	EA6.73.278	Spares for:-						-	-	-	-
		BRACKET, bottom						1	DTD610	C	Q.2
		Attachment of bottom bracket to fixed fairing						-	-	-	-
28D/9133012	A25/3C	Bolt, 2BA						2	-	C	Q.2
5970	EA6.73.93	Washer						2	-	C	Q.2
1413	EA1.20.6817	PANEL, Access, Group						1	-	B	Q.2
		Spares for:-						-	-	-	-
28FP/4062619	Oddie 217/2	STUD						2	-	C	Q.2
	Oddie							-	-	-	-
28FP/1004893	214	WASHER						2	-	C	Q.2
13862	EB8.20.4858	PANEL, access						1	L72	C	Q.2
		Attachment of access panel to fixed fairing						-	-	-	-
6217	EBAS.1/1E	Screw, $\frac{1}{4}$ in. BSF						15	S96	C	Q.2
21721	EA3.20.2870	PANEL, Hinged, Group						1	-	B	Q.1
		Spares for:-						-	-	-	-
	EA1.20.1679	HINGE, (Make from Ref. 28N/10363)						1	-	LM	Q.1
3026	EA1.20.1676	PANEL, hinge (16 swg)						1	DTD610	C	Q.1
1887	EA1.40.436	SPRING						2	Spring Steel	C	Q.1
	EA3.20.1627	SEAL, rubber, 90 in. long (make from Ref.4432)						1	-	LM	Q.2
		Attachment of fixed fairing to oleo leg						-	-	-	-
4174	EA1.40.519	Bolt, $\frac{5}{16}$ in. BSF						8	-	C	Q.1
28W/1086617	AGS 162/E	Washer, spring,						8	-	C	Q.1

UNDERCARRIAGE
MAIN UNDERCARRIAGE - STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
5797	EA6.40.8						LEG, Sliding and Oleo Head, Group (Pre Mod 3211)	1	-	A	Q.1.3
32315	EA9.40.24						LEG, Sliding and Oleo Head Group (Mod 3211 Pre Mod 4270)	1	-	A	Q.1.3
34713	EA9.40.60						LEG, Sliding and Oleo Head Group (Mod 4270)	1	-	A	Q.1.3
660	EA1.40.639						Spares for:- BRACKET, angle, micro switch, mounting Attachment micro switch angle bracket to top torque link	1	DTD390	C	Q.1.2
28D/9140638	A25/4B						Bolt, 4BA	4	-	C	Q.2
28M/9403519	A27/BP						Nut, 4BA	4	-	C	Q.2
706	EA1.40.335						Plate, packing	1	Lam.Alum	C	Q.2
28W/9416642	SP47/B						Washer, spring, 4BA	4	-	C	Q.2
662	EA1.40.671						FINGER, operating, micro switch Attachment of micro switch operating finger to oleo head	1	L40	C	Q.2
28S/9435713	A31/C20						Screw, 2BA	2	-	C	Q.2
28W/9416643	SP47/C						Washer, spring, 2BA	2	-	C	Q.2
-	-						HEAD, Oleo Assembly (EA6.40.4) (Pre Mod 4270)	-	-	-	Q.3
-	-						HEAD, Oleo Assembly (EA9.40.58) (Mod 4270)	-	-	-	Q.3
663	EA1.40.89						Spares for:- BALL, side stay joint Attachment of ball to oleo head group	1	S11	C	Q.3
664	EA1.40.101						Bush, bearing	1	DTD412	C	Q.3
675	EA1.40.96						Ring, retaining	1	DTD124	C	Q.3
677	EA1.40.98						Ring, retaining	1	DTD124	C	Q.3
680	EA1.40.99						Stud	12	S11	C	Q.3
665	EA1.40.109						BUSH, pivot	2	DTD412	C	Q.3
666	EA1.40.111						BUSH, torque link lug Attachment of torque link bush to oleo head	2	DTD412	C	Q.3
673	EA1.40.679						Plug	2	L40	C	Q.3
21482	EA1.40.20						FORGING, Oleo head (Pre Mod 4270)	1	-	C	
42059	EA9.40.56						FORGING, oleo head (Mod 4270)	1	-	C	
28N/9156370	SP21						NIPPLE, grease	2	-	C	Q.3
20656	EA1.40.127						PIPE, stack, group	1	-	C	Q.3
-	-						PISTON, Assembly (EA6.40.6)	-	-	C	Q.3
670	EA1.40.647						Spares for:- PISTON Attachment of piston to strut	1	DTD197	C	Q.3

RESTRICTED

UNDERCARRIAGE

MAIN UNDERCARRIAGE - STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Expt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
1099	EEAS 37/22A							2	S11	C	Q.3
	EEAS 38/3A							1	S11	LM	Q.3
22528	EA6.40.33							1	S96	C	Q.3
683	EA 1.40.61							3	S11	C	Q.3
672	EA1.40.651							1	BESA 4K6	C	Q.3
28Y/9701165	AGS2096							1	-	B	Q.3
28D/1215078	AS1246/5C							1	-	C	Q.3
	-							1	-	LM	-
669	EA1.40.103							1	M.S.Wire	C	Q.3
28P/9486478	SP90/C5							1	-	C	Q.3
681	EA1.40.105							L	L40	C	Q.3
28F/8014021	AGS1138/B							1	-	C	Q.3
682	EA1.40.149							1	DTD124	C	Q.3
28W/9416643	SP47/C							1	-	C	Q.3
-	-							-	-	-	Q.3
-	-							-	-	-	Q.3
26640	EA3.40.201							1	S95 or S96	C	Q.3
2467	EA3.40.45							1	-	C	Q.3
684	EA1.40.161							2	DTD412	C	Q.3
	EA3.40.217							1	-	-	Q.3
21355	EA3.40.23							1	L40	C	Q.3
13024	EA3.40.183							1	S96	C	Q.3
1753	EA3.40.19							1	S96	C	Q.3
21537	EA3.40.21							1	L40	C	Q.3
28M/1011476	A27/JS							1	-	C	Q.3
28P/1040788	SP90/C8							1	-	C	Q.3
28W/9419466	SP13/J							1	-	C	Q.3
1463	EA3.40.10							1	-	A	Q.3
691	EA1.40.41							1	S11	C	Q.3
692	EA1.40.653							1	DTD197	C	Q.3
37461	EA3.40.219							1		C	Q.3
693	EA1.40.175							1	S97	C	Q.3
694	EA1.40.655							1	DTD683	C	Q.3
NOTE:- * 26FZ/692 EA1.40.655 still required: 26FZ/37461 EA3.40.219 found unsuitable as a spare:											

UNDERCARRIAGE
MAIN UNDERCARRIAGE - STARBOARD

Ref. No	Part No.							Description	No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6					
14701	EA3.40.203							PIUG, oleo base (Mod 2760)	1	DTD683	C	Q.3
695	EA1.40.677							PIUG, pivot bearing bush	2	L40	C	Q.6
14705	EA3.40.215							RING, backing (Mod 2760)	2	Fabric	C	Q.3
12913	EA1.40.657							RING, distance	1	DTD683	C	Q.3
697	EA1.40.57							RING, piston	1	BESA 4K6	C	Q.3
12915	EA1.40.45							RING, retaining	1	S3	C	Q.3
696	EA1.40.37							RING, sealing, rubber (Pre Mod 2760)	2	Shore Hardness 70	C	Q.3
698	EA1.40.661							RING, sealing, rubber (Pre Mod 2760)	1	Shore Hardness	C	Q.3
14703	EA3.40.213							RING, sealing, rubber (Mod 2760)	2	S80	C	Q.3
14704	EA3.40.211							RING, sealing rubber (Mod 2760)	1	S15	C	Q.3
14702	EA3.40.205							RING, sealing, rubber (Mod 2760)	1	S15	C	Q.3
21354	EA1.40.659							RING, stop, shock absorber	1	DTD683	C	Q.3
21221	EA1.40.635							RING, SPACER (Pre Mod 2760)	2	DTD138	C	Q.3
699	EA1.40.165							SCREW, grub, piston locking (Pre Mod 3211)	1	S1	C	Q.3
32210	EA3.40.221							Pin, locking, piston (Mod 3211)	1		C	Q.3
700	EA1.40.167							SCREW, grub, stopnut locking	1	S1	C	Q.3
14706	EA1.40.209							SEAL, housing (Mod 2760)	1	L65	C	Q.3
14700	EA3.40.207							SPACER (Mod 2760)	1	L1	C	Q.3
683	EA1.40.61							STUD, orifice plate	6	S11	C	Q.3
701	EA1.40.39							WASHER, fibre	1	BS126	C	Q.3
702	EA1.40.43							WASHER, packing, 3/16 in.	1	Hard Felt	C	Q.3
3632	EA1.40.28							LINK, torque top Attachment of top torque link to oleo head	1	DTD683	C	Q.3
704	EA1.40.69							Pin, bearing	1	S11	C	Q.3
707	EA1.40.77							Screw, 1 in. BSF	1	S11	C	Q.3
708	EA1.40.139							Screw, locking, 1/4 in. BSF.	1	S1	C	Q.3
709	EA1.40.619							Shim	1	Lam. Alum.	C	Q.3
711	EA1.40.73							Sleeve	1	S11	C	Q.3
713	EA1.40.75							Washer, bearing	1	DTD412	C	Q.3
718	EA1.40.147							Washer, bearing	1	DTD412	C	Q.3
714	EA1.40.79							Washer, locking	1	DTD124	C	Q.3
3631	EA1.40.27							LINK, torque bottom Attachment of bottom torque link to oleo sliding leg	1	DTD683	C	Q.3
703	EA1.40.67							Pin, bearing	1	S11	C	Q.3
707	EA1.40.77							Screw, 1 in. BSF	1	S11	C	Q.3
708	EA1.40.139							Screw, locking, 1/4 in. BSF	1	S1	C	Q.3
709	EA1.40.619							Shim	1	Lam. Alum	C	Q.3
710	EA1.40.71							Sleeve	1	S11	C	Q.3
713	EA1.40.75							Washer, bearing	1	DTD412	C	Q.3
718	EA1.40.147							Washer, bearing	1	DTD412	C	Q.3
714	EA1.40.79							Washer, locking	1	DTD124	C	Q.3
								Attachment of top and bottom torque links				
661	EA1.40.153							Bush, bearing	1	DTD412	C	Q.3
28N/9156370	SP21							Nipple, grease	1	-	C	Q.3
28M/4095931	A27/SS							Nut, slotted, 3/4 in. BSF	1	-	C	Q.3
1500	EA3.40.27							Pin, bearing	1	S97	C	Q.3
28P/221916	SP90/G14							Pin, split, 1/8 in. dia	1	-	C	Q.3
715	EA1.40.83							Washer	1	S11	C	Q.3
1514	EA3.40.29							Washer	1	S96	C	Q.3
1515	EA3.40.31							Washer	1	S96	C	Q.3

RESTRICTED

UNDERCARRIAGE
MAIN UNDERCARRIAGE - STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
28N/9156370	SP21						NIPPLE, grease	4	-	C	Q.3
712	EAL.40.137						TAB, locking	1	S3	C	Q.3
							Attachment of locking tab to oleo head				
28S/1200034	A31/B16						Screw, 4BA	1	-	C	Q.3
28W/9416642	SP47/B						Washer, spring, 4BA	1	-	C	Q.3
							Attachment of sliding leg and oleo head group to wheel and wheel brake unit				
2168	EA6.40.35						Bolt, 1/2 in. BSF	10	S97	C	Q.1
28M/4095892	A27/NS						Nut, slotted, 1/2 in. BSF	10	-	C	Q.1
28P/9525532	SP90/E10						Pin, split, 3/32 in. dia.	10	-	C	Q.1
2169	EA3.40.43						Washer, 1/2 in.	10	DTD124	C	Q.1
13859	EB8.40.21						LEVER, Cowl Door Mechanism Group	1	-	B	Q.1,2
							Spares for:				
13860	EB8.40.25						HINGE, group	1	-	C	Q.2
							Attachment of hinge to cowl door mechanism lever				
28M/1278190	AGS2001/C1						Nut, stiff, 2BA	1	-	C	Q.2
13861	EB8.40.33						Pin, hinge	1	S95	C	Q.2
28W/9419475	SP15/C						Washer, 2BA	1	-	C	Q.2
							Attachment of cowl door mechanism lever to oleo leg group				
30827	EB8.40.113						Bolt, 1/2 in. BSF	4	-	C	Q.2
	Dunlop										
27G/6325453	AHM2576						PIPE, feed for maxaret unit	1	-	C	Q.1
	Dunlop										
27G/2488	AHM2578						PIPE, feed for maxaret unit	1	-	C	Q.1
	Dunlop										
27A/1450834	DT1609						TUBE, 43 in. x 12.5 in. x 21 in. (Mod 4386)	1	-	A	Q.1
	Dunlop										
27A/4560809	DR1623						TYRE, 43 in. x 12.5 in. x 21 in.	1	-	A	Q.1
	or										
	Good Year										
	GA.1266										
	or										
	Firestone										
	ZA.303										
	Dunlop										
27G/4617714	AC11514						UNIT, maxaret, automatic brake control (for spares see SP4515C, Vol 3 Pt 1 Section 2)	1	-	A	Q.1
	Dunlop										
27A/1450713	AH52692						WHEEL, undercarriage (Mod 4386)	1	-	A	Q.1
34173	EA9.40.44						STAY, Side, Undercarriage, Starboard Group (Mod 3585 Pre Mod 5051)	1	-	A	Q.1,2
6119300	EA9.40.74						STAY, Side, Undercarriage, Starboard Group (Mod 5051)	1	-	A	Q.1,2
							Spares for:				
529	EAL.40.239						BOLT, stop, 11/16 in. BSF	1	S97	C	Q.2
							Attachment of stop bolt to link stay bracket				
537	EAL.40.353						Nut, 11/16 in. BSF	1	S11	C	Q.2

UNDERCARRIAGE
MAIN UNDERCARRIAGE-STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqp't. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
530	EAL.40.405						BOLT, $\frac{5}{16}$ in. BSF	1	S96	C	Q.2
							Attachment of bolt to sequence valve operating bracket				
28M/1011470	A27/GT						Locknut, $\frac{5}{16}$ in. BSF	1	-	C	Q.2
7112	EAL.40.229						BRACKET, solenoid operating stud	1	S96	C	Q.2
							Attachment of stud bracket to side stay				
28D/1011310	A25/8L						Bolt, $\frac{7}{16}$ in. BSF	2	-	C	Q.2
28D/1212690	A25/15L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28D/1212688	A25/18L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28M/9129449	A27/L8						Nut, slotted, $\frac{7}{16}$ in. BSF	4	-	C	Q.2
28P/9525532	SP90/E10						Pin, split, $\frac{3}{32}$ in. dia.	4	-	C	Q.2
32721	EAL.40.404						BRACKET, sequence valve operating stud	1	L40		Q.2
							Attachment of stud bracket to side stay				
28D/9133011	A25/2C						Bolt, 2BA	1	-	C	Q.2
28D/1212688	A25/18L						Bolt, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28W/1006940	1110						Lockwasher, "shakeproof"	1	-	C	Q.2
28M/9122449	A27/L8						Nut, slotted, $\frac{7}{16}$ in. BSF	1	-	C	Q.2
28P/9525532	SP90/E10						Pin, split, $\frac{3}{32}$ in. dia.	1	-	C	Q.2
531	EAL.40.199						LEVER, Undercarriage Lock, Group	1	-	B	Q.2
							Spares for:-				
532	EAL.40.213						BUSH	1	DTD197	C	Q.2
533	EAL.40.200						LEVER, Undercarriage Lock, Group	1	-	B	Q.2
							Spares for:-				
532	EAL.40.213						BUSH	1	DTD197	C	Q.2
							Attachment of undercarriage lock levers to side stay				
525	EAL.40.195						Bolt, $\frac{3}{8}$ in. BSF hook catch pin	1	S65	C	Q.2
28N/9156370	SP21						Nipple, grease	18	-	C	Q.2
22176	EAL.40.351						Nut, slotted, $\frac{5}{8}$ in. BSF	1	-	C	Q.2
28P/1221023	SP90/G12						Pin, split, $\frac{1}{8}$ in. dia.	1	-	C	Q.2
543	EAL.40.219						Tube, distance	1	L40	C	Q.2
544	EAL.40.291						Washer, tab	1	S3	C	Q.2
547	EAL.40.417						Washer, under tab washer	1	DTD390	C	Q.2
28W/9419481	SP15/Q						Washer, $\frac{5}{8}$ in.	1	-	C	Q.2

RESTRICTED

UNDERCARRIAGE
MAIN UNDERCARRIAGE - STARBOARD

Ref. No	Part No.	Description						No. off	Material Specification	Class of Eqpt. M.R. or L.M.	Plate No.
		1	2	3	4	5	6				
13169	EA3.40.192						LEVER, Micro Switch Operating Group Spares for:-	1	-	C	Q.2
179	EA1.40.569						SCREW, tappet Attachment of tappet screw to operating lever	1	S11	C	Q.2
28M/1007403	A27/ET						Locknut, $\frac{1}{4}$ in. BSF Attachment of micro switch operating lever to side stay	1	-	C	Q.2
528	EA1.40.221						Bolt, $\frac{3}{8}$ in. BSF	1	S65	C	Q.2
28N/9155370	SP21						Nipple, grease	1	-	C	Q.2
26667	EA3.40.193						Nut, slotted, $\frac{3}{8}$ in. BSF	1	-	C	Q.2
542	EA1.40.217						Tube, distance	1	L40	C	Q.2
545	EA1.40.355						Washer	1	DTD390	C	Q.2
6472	EA1.40.225						LINK, Side Stay, Group Spares for:	1	-	B	Q.1,2
536	EA1.40.227						BUSH, bearing Attachment of link to side stay	2	DTD197	C	Q.2
526	EA1.40.197						Bolt, 1 in. BSF	1	S65 or 81	C	Q.2
28N/9156370	SP21						Nipple, grease	1	-	C	Q.2
12916	EA1.40.347						Nut, slotted, 1 in. BSF	1	-	C	Q.2
538	EA1.40.223						Plug, adaptor, for grease nipple	1	L40	C	Q.2
28P/1209392	SP90/K20						Pin, split, 3/16 in. dia.	1	-	C	Q.2
37307	EA1.40.765						Washer	1	-	C	Q.2
539	EA1.40.205						ROLLER, stop lever, group Attachment of roller to stop lever	1	-	C	Q.2
527	EA1.40.203						Bolt, $\frac{3}{8}$ in. BSF	1	S96	C	Q.2
40530	EA1.40.349						Nut, slotted, $\frac{3}{8}$ in. BSF. (make from 28M/13123)	1	-	LM	Q.2
28P/1040788	SP90/C8						Pin, split, 1/16 in. dia.	1	-	C	Q.2
7113	EA1.40.233						SLEEVE, operating spring, for undercarriage uplock	1	L40	C	Q.2
540	EA1.40.237						SPRING, compression at lock stop	1	Spring Steel Wire	C	Q.2
40651	EA9.40.40						STAY, side starboard (Mod 3585 Pre Mod 5051)	1	-	B	-
6119309	EA9.40.80						STAY, side starboard (Mod 5051)	1	-	B	-
541	EA1.40.235						STOP, undercarriage lock (For attachment main undercarriage to wing. See Section HA)	1	S11	C	Q.2