

AIRFRAME MP 17(1) (1 and 2)		MAINTENANCE PROCEDURES COMPONENT REPLACEMENTS CANBERRA PR9		AP101B-0409A-5A3A 2nd Edition Sect 1 Chap 1		Maintenance Record Aircraft or Equipment Serial No:		MOD Form 707MS (Revised Jan 01) Date:			
PORT ELEVATOR - FITTING											
INFORMATION IN THE TOPIC 5A2 IS TO BE CONSULTED THROUGHOUT THE WORK DETAILED ON THIS CARD						Tradesman		Brief Details of		Supervisor	
Associated Procedures						Code	Man Hrs	Certification and TDM	suspected fault(s) and SNOW(s)	Man Hrs	Certification and TDM
MP 28 and 225											
<u>Special Tools and Equipment:</u> Nil.											
BLOCK 1 AIRFRAME											
1. <u>Fitting</u> Before carrying out Sub-item 1.1 the balance weight and arm is to be positioned in the aircraft tail section.											
1.1 Elevator. (i) Position. (ii) Move inboard to engage inboard and outboard hinge pins.											
1.2 Balance weight and arm.)											
1.3 Centre hinge bracket.) Refit.											
1.4 Centre hinge bracket bolt)											
(3 off).)											
1.5 Centre hinge bracket nut (i) Refit.											
(3 off). (ii) Lock with split pin.											
1.6 Balance weight washer. Refit.											
1.7 Balance weight nut. (i) Refit.											
(ii) Lock with split pin.											
When carrying out Sub-item 1.8 the aft bolt is to be located with bolt head to port.											
1.8 Coupling link.) Reconnect.											
1.9 Control tube.)											
E0393(47) Continued											

[illegible]