

POWER INSTALLATION—GEARBOX AND ACCESSORIES

| Ref. No.       | Part No.          | Description   | No. Off | Material Specification | M.R. Class of Store | Plate No. |
|----------------|-------------------|---|---------|------------------------|---------------------|-----------|
|                |                   |   |         |                        |                     |           |
|                | D.187592          | ACCESSORY DRIVE FOR GEARBOX AND EQUIPMENT, ASSEMBLY       | —       | —                      |                     |           |
|                | 412 F.187588      | Block, clamp (in halves)                                  | 1       | DTD.364                | C.                  | LB.1      |
|                | 414 F.187781      | Bolt, special, for securing hydraulic pump                | 4       | S.94.B                 | C.                  | LB.1      |
|                | 415 F.187782      | Bolt, special   | 2       | S.94.B                 | C.                  | LB.1      |
|                | 420 F.188684      | Bolt, "U", supporting driving shaft at frame 34           | 1       | S.1                    | C.                  | LB.1      |
|                | 6395 F.188685     | Channel, stop   | 1       | DTD.610                | C.                  |           |
|                | F.260908          | Clip, bracket (AS.1150/97)                                | 2       | S.510 or C.511         |                     |           |
| 24             | 37L/306 GD9/107   | Drive shaft and engine coupling, paired units (Mod. 1445) | 1       |                        | A.                  |           |
|                | 37L/4521650 —     | Gearbox, accessories drive, type T.G5/8                   | 1       | —                      | A.                  |           |
|                | 416 A.187589      | Eye-end, supporting generators                            | 1       | Stamping               | C.                  | LB.1      |
|                | 417 A.187590      | Fork-end, at stringer "K", supporting generators          | 1       | S.94.B                 | C.                  | LB.1      |
|                | 5UA/4357526 —     | Generator, type 515A                                      | 2       | —                      | A.                  |           |
|                | 418 F.188834      | Nut, lock, for generator support, at stringer "K"         | 1       | S.1                    | C.                  | LB.1      |
|                | 6104 F.209992     | Piece, distance, between gearbox and spar                 | 1       | DTD.610                | C.                  |           |
| 24             | 37J/4602111 Dowty | Pump, hydraulic, type A8003, Y/R.H./3000                  | 1       | —                      | A.                  |           |
|                | Std.1509/23/075   | Tube, distance, at "U" bolt                               | 2       | T.4                    |                     | 4         |
|                | Std.914/J/14      | Washer, at generator lug                                  | 1       | S.1                    |                     | 4         |
|                | 5781 Std.915/E/20 | Washer  | 2       | DTD.610                | C.                  | 4         |
|                | 3953 Std.915/E/22 | Washer, (shim)  | 1       | DTD.610                | C.                  | 4         |
| 37L<br>4521250 |                   | HYD PUMP QUILL DRIVE                                      |         |                        |                     |           |





This file was downloaded  
from the RTFM Library:

Link: [www.scottbouch.com/rtfm](http://www.scottbouch.com/rtfm)

Please see site for usage terms,  
and more aircraft documents.

