

FUSELAGE
ASSEMBLY OF AIR BRAKE TO FUSELAGE, PORT

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip.	Plate No.
					M.R. L.M.	
		1 2 3 4 5 6				
	—	ASSEMBLY OF AIR BRAKE TO FUSELAGE, PORT (E.B2.11.14431) Consisting of:—	—	—	—	4/42
4315	E.B2.11.14251	. BOLT, hinge, lower bearing	1	S97	C	4/48
4316	E.B2.11.14253	. BOLT, hinge, upper bearing	1	S97	C	4/47
69	E.B2.11.14429	. DOOR, air brake, group	1	—	A	4/34
		Spares for:—				
28842	E.B2.11.14237	. . BEARING, upper hinge, air brake door, group	1	—	B	4/52
		Spares for:—				
4318*	TORRINGTON	. . . BEARING, needle roller	2	—	B	4/44
2A/8059324	B.912					
4320	E.B2.11.14243	. . . TUBE, distance	1	L56	C	4/46
		Attachments:—				
28M/9480017	AGS.2001/E/1	. . Nut, stiff, 1/4" BSF	8	—	C	4/56
26FZ/1032	EEAS.1/2E	. . Screw, 1/4" BSF 120° c'sk head	8	S96	C	4/54
28W/9418921	SP13/E	. . Washer, 1/4" BSF plain	8	—	C	4/55
	E.B2.11.14441	. . BEARING, lower hinge, air brake door, group	1	—	—	4/53
		Spares for:—				
4318*	TORRINGTON	. . . BEARING, needle roller	2	—	B	4/50
2A/8059324	B.912					
4319	E.B2.11.14241	. . . TUBE, distance	1	L56	C	4/49
		Attachments:—				
28M/9480017	AGS.2001/E/1	. . Nut, stiff, 1/4" BSF	8	—	C	4/59
26FZ/1032	EEAS.1/2E	. . Screw, 1/4" BSF 120° c'sk head	8	S96	C	4/57
28W/9418921	SP13/E	. . Washer, 1/4" BSF plain	8	—	C	4/58
4317	E.B2.11.12993	. . BLOCK, trunnion bearing	1	—	C	4/65
		Attachments:—				
28D/1011238	A25/3E	. . Bolt, 1/4" BSF hex. head	1	—	C	4/31
28D/1008151	A25/4E	. . Bolt, 1/4" BSF hex. head	6	—	C	4/29
28W/9419405	SP15/E	. . Washer, 1/4" BSF plain	3	—	C	4/30
4322	E.B2.11.12994	. . BLOCK, trunnion bearing	1	—	C	4/61
		Attachments:—				
28D/1011238	A25/3E	. . Bolt, 1/4" BSF hex. head	1	—	C	4/31
28D/1008151	A25/4E	. . Bolt, 1/4" BSF hex. head	6	—	C	4/29
28W/9419405	SP15/E	. . Washer, 1/4" BSF plain	3	—	C	4/30
4323	E.B2.11.4969	. . BRACKET, synchronising link attachment	1	—	C	4/72
		Attachments:—				
26FZ/1034	EEAS.1/3E	. . Screw, 1/4" BSF 120° c'sk head	4	S96	C	4/71
4325	E.B2.11.12803	. . BUSH, spherical, trunnion block	2	S97	C	4/69
28N/1007712	AGS.2031/24	. . CIRCLIP, trunnion securing	1	—	C	4/66

Restricted

Page HA2

**FUSELAGE
ASSEMBLY OF AIR BRAKE TO FUSELAGE, PORT**

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip.	Plate No.
					M.R. L.M.	
		1 2 3 4 5 6				
4326	E.B2.11.14443	. . . LATCH, air brake door, group Spares for:—	1	—	B	4/87
28D/1214865	AS.1246/2B	. . . BOLT, 4 BA round head, pivot bracket mounting	1	—	C	4/90
28D/9130082	AS.1246/3B	. . . BOLT, 4 BA round head, pivot bracket mounting	1	—	C	4/89
	E.B2.11.14445	. . . BRACKET, plunger and micro-switch connecting levers pivot	1	L65	—	4/94
13454	E.B2.11.5235	. . . COLLAR, micro-switch tappet	1	L40	C	4/92
	E.B2.11.5227	. . . LEVER, plunger and micro-switch connecting	1	L65	—	4/79
28M/9403519	A27/BP	. . . NUT, 4 BA plain, for pivot bracket mounting bolt	2	—	C	4/81
	E.B2.11.5229	. . . PIN, roller plunger	1	L65	—	4/82
4328	E.B2.11.5231	. . . PIN, tappet, micro-switch	1	L65	C	4/96
28P/1009706	SP4Y/A2	. . . PIN, shackle, plunger and micro-switch tappet to lever connecting	2	—	C	4/75
28P/1013114	SP4Y/B8	. . . PIN, shackle, lever pivot	1	—	C	4/80
28P/1021104	SP90/C3	. . . PIN, split, pivot pin retaining	3	—	C	4/76
4329	E.B2.11.5233	. . . SPRING, micro-switch tappet loading	1	Spring Steel	C	4/83
4331	AS.2808/5/015	. . . TUBE, distance	2	—	C	4/78
	AS.2809/3/041	. . . TUBE, distance	1	—	—	4/84
28W/9419465	SP13/B	. . . WASHER, 4 BA plain, plunger and micro-switch tappet thrust and bracket mounting	2	—	C	4/77
28W/9419402	SP13/C	. . . WASHER, 2 BA plain, pivot pin thrust Attachments:—	3	—	C	4/95
28D/9133011	A26/2C	. . . Bolt, 2 BA hex. head	1	—	C	4/93
28D/9133012	A25/3C	. . . Bolt, 2 BA hex. head	2	—	C	4/91
28D/1200119	A25/4C	. . . Bolt, 2 BA hex. head	1	—	C	4/88
10032	EEAS.296/22/40C	. . . Bolt, 2 BA special	1	S97	C	4/85
10015	EEAS.296/27/40C	. . . Bolt, 2 BA special	1	S97	C	4/86
26FZ/1102	EEAS.41/2	. . . PIN, sealing	16	—	C	4/43
26FZ/5073	EEAS.65	. . . PLATE, serial number	1	—	C	4/64
5993	E.B2.11.15331	. . . SHIM, laminated, at bearing blocks	2	—	C	4/33
	E.B2.11.1971	. . . SKIN, outer	1	L65	—	4/35
	E.B2.11.1973	. . . SKIN, inner	1	L65	—	4/36
	E.B2.07.915	. . . SKIN, inner (E.B2.11.1975)	1	L65	—	4/37
	E.B2.11.2503	. . . SKIN, inner, upper	1	L65	—	4/38
	E.B2.11.17069	. . . SKIN, outer	1	L65	—	4/39

Restricted

BD

FUSELAGE
ASSEMBLY OF AIR BRAKE TO FUSELAGE, PORT

Ref. No.	Part No.	Description 1 2 3 4 5 6	No. off	Mtl. Spec.	Cl. of Equip.	Plate No.
					M.R. L.M.	
19198	E.B2.11.18099	. . . TRUNNION, door operating jack attachment, assembly Spares for:—	1	—	B	4/67
28N/9156370	SP21	. . . NIPPLE, grease	2	—	C	4/63
20260	E B2.11.18091	. . . PLUG	2	S92	C	4/62
18695	E B2.11.18085	. . . TRUNNION	1	S99	C	4/70
28N/9156370	SP21	. NIPPLE, grease	2	—	C	4/40
28FP/9482442	AVIAN. DEVELS. A419	. PIN, "pip," quick release	2	—	C	4/41
4345	E B2.11.14245	. TUBE, distance, lower bearing hinge bolt	1	S82	C	4/51
4346	E.B2.11.14247	. TUBE, distance, upper bearing hinge bolt	1	S82	C	4/45
4333	E.B2.11.15593	. UNIT, lock, air brake door, assembly Spares for:—	1	—	B	4/26
2967	E B1.20.7623	. . BOLT, special, plunger operating lever jack attachment	1	S96	C	4/3
21475	E B2.07.717	. . CHANNEL, and bearing, assembly (E.B2.11.5189) Attachments:—	1	—	C	4/22
28D/9436920	A25/1C	. . Bolt, 2 BA hex. head	3	—	C	4/25
28D/9133012	A25/3C	. . Bolt, 2 BA hex. head	1	—	C	4/8
28M/1278190	AGS 2001/C/1	. . Nut, stiff, 2 BA	4	—	C	4/23
28W/9419402	SP13/C	. . Washer, 2 BA plain	4	—	C	4/24
6012	E.B2.11.15583	. . CHANNEL, and bearing, assembly Spares for:—	1	—	C	4/11
	E F3 25.113	. . . NUT, anchor, corner, 1/4" BSF Attachments:—	2	—	—	4/27
28D/9133014	A25/13C	. . Bolt, 2 BA hex. head	2	—	C	4/4
	AS.2806/4/115	. . Tube, distance	2	—	—	4/16
6125	GEO. SALTER 5100/31	. . CIRCLIP, truarc, plunger operating lever pivot pin retaining	1	—	C	4/19
5K/9132076	HELLERMANN HT.0813/3/C	. . CLIP, cable securing	1	—	C	4/10
13460	E.B2.11.15585	. . LEVER, c/w bush, plunger operating	1	—	C	4/1
28N/9156370	SP21	. . NIPPLE, grease, for plunger operating jack attachment bolt	1	—	C	4/2
4335	E.B2.11.5215	. . PIN, anchor, air brake door lock nut, hydraulic jack (Make from SP4Y/H20) Attachments:—	1	—	C	4/7
28P/9554984	SP90/E7	. . Pin, split	1	—	C	4/6
28W/9419489	SP16/J	. . Washer, 3/8" BSF plain	1	—	C	4/5

Restricted

Page HA4

**FUSELAGE
ASSEMBLY OF AIR BRAKE TO FUSELAGE, PORT**

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip.	Plate No.
					M.R. L.M.	
		1 2 3 4 5 6				
4336	E.B2.11.5219	. . . PIN, pivot, for plunger operating lever	1	S96	C	4/17
28670	E.B2.11.12739	. . . PLUNGER, air brake door lock unit	1	L65	C	4/20
4337	E.B2.11.5217	. . . ROLLER, micro-switch operating lever link	1	S97	C	4/13
		Attachments:—				
28D/1012221	SP4Y/B12	. . . Pin, shackle	1	—	C	4/12
28P/1021104	SP90/C3	. . . Pin, split	1	—	C	4/14
28W/9419402	SP13/C	. . . Washer, 2 BA plain	1	—	C	4/15
4338	E.B2.11.5187	. . . SPRING, compression, plunger loading	1	Spring Steel	C	4/21
13462	AS.2808/7/05	. . . TUBE, distance, plunger operating lever	1	—	C	4/18
35024	E.B2.11.18257	. . . UNIT, micro-switch, group	1	—	A	5/20
		Spares for:—				
	E.B2.11.14421	. . . BARREL, operating plunger	1	S94 or S117	—	5/8
4340	E.B2.11.5183	. . . BOLT, special, 8 BA micro-switch	2	S95	C	5/5
5E/3876	†	. . . CABLE, uniefglass 20	QR	—	C	5/13
8723	GEO. SALTER 5100/43	. . . CIRCLIP, truarc	1	—	C	5/4
19797	E.B2.11.18097	. . . LEVER, trip	1	S15	C	5/18
		Attachments:—				
28P/1207870	SP4Y/B11	. . . Pin, shackle	1	—	C	5/2
28P/1021104	SP90/C3	. . . Pin, split	1	—	C	5/3
28W/9419402	SP13/C	. . . Washer, 2 BA plain	1	—	C	5/6
4342	E.B2.11.14423	. . . SPINDLE, operating, plunger	1	S95	C	5/7
4343	E.B1.11.4327	. . . SPRING, 18 SWG	1	Spring Steel	C	5/9
5CW/4632	B.T.H.	. . . SWITCH, type L.H.E. 11.A1/3	1	—	A	5/15
	CX.116667					
5X/9462951	HELLERMANN HC.294	. . . TERMINAL, ring tongue	2	—	C	5/12
4331	AS.2808/5/015	. . . TUBE, distance	2	—	C	5/11
4344	E.B2.11.5185	. . . WASHER, special, 18 SWG	2	L72	C	5/14
		Attachments:—				
28D/9436920	A25/1C	. . Bolt, 2 BA hex. head	4	—	C	5/19
9340	EEAS.238/2A	. . WASHER, "D", cable clip spacing	1	L72	C	4/9
		Attachments:—				
28D/1011030	A25/2E	. Bolt, 1/4" BSF hex. head	2	—	C	4/28
30A/3055	†	. WIRE, locking, 22 SWG	QR	DTD189	C	4/60

Restricted

BD