

CHAP	5	SP 506	SERVICING PROCEDURES						AP 101B-1000-5A3 E (Section 1 (1st Edition))				TIME	ACT		
TRADE	FLT SYST			LIGHTNING												
SHEET	1	OF	16	SHEET/S		3		5	6	AL NO	12	DATE				
TITLE	FCS Computer Type 'D'									SERVICING RECORD - RAF F.2988B AC NO DATE					EST	
Safety and Servicing Notes are to be complied with throughout the work detailed on this Card.										(1)	(2)	(3)	(4)	(5)		
Special Tools and Equipment										MAN HOURS	TRADESMEN INIT	BRIEF DETAILS OF OR SUSPECTED DEFECT	F. 720B NO	N.C.O. INITIALS	ASSOCIATED PROCEDURE CARDS	
Test Set Type 8A. Test Set Pitot/Static Mk 4 or 5. Test Set Mk 2 MRG 1st Line. Test Set Type 391 ILS.																
NB This Procedure is applicable only if a serviceable component is replaced in a known serviceable system. ▶◀ <p style="text-align: center;">FLT SYST</p> <ol style="list-style-type: none"> 1. <u>Preparation</u> <ol style="list-style-type: none"> 1.1 Pitot/Static test set. Connect to aircraft. 1.2 Type 8A test set. <ol style="list-style-type: none"> (i) Connect to aircraft test socket J, F and L. (ii) Connect to test socket FC5 and FCC. 1.3 MRG Mk 2 1st line test set. Connect to electronic unit test socket Q. 1.4 External power supplies. (A.c. and d.c.). <ol style="list-style-type: none"> (i) Connect to aircraft. (ii) Set to 'ON'. 1.5 Instrument master switch.) 1.6 MRG On/Off switch.) Set to 'ON'. 1.7 PCU master switch.) 1.8 Height display unit. Set to zero ft. 1.9 Type 8A test set. Set to 'AP HEIGHT'. 																
SMS/80/453/19										Continued					SP NO	506

CHAP	5	FLT SYST	SERVICING PROCEDURES		AP101B-1000-5A3 E				
SP NO	506	CONTINUED	LIGHTNING		Section 1 (1st Edition)				
SHEET	2	AL 12			AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.					SERVICING RECORD				
					(1)	(2)	(3)	(4)	(5)
FLT SYST									
1. <u>Preparation</u> (Contd)									
1.10 ILS test set (i) Position as near to localizer aerials as possible									
Type 391. (ii) Connect supply ensuring correct polarity.									
2. <u>Interlock Checks</u>									
2.1 Pilots control unit. (PCU).									
(a) Master switch.) Set to 'OFF'.									
(b) Stab switch.)									
2.2 FD/AP switch. Set to 'OFF'.									
2.3 PCU.									
(a) Supplies) Ensure show Off.									
M1.)									
(b) Mode M1.)									
2.4 FD bead. Ensure in parking position.									
2.5 PCU.									
(a) Master switch. (i) Set to 'ON'.									
(ii) Allow 3 minutes to warm up.									
(b) Supplies Ensure shows Black.									
M1.									
(c) Mode M1. Ensure shows Off.									
2.6 FD bead. Ensure in parking position.									
2.7 PCU attitude swtich. Select.									
2.8 FD/AP switch. Set to 'AP'.									
2.9 PCU.									
(a) Supplies.) Ensure show Off.									
M1.)									
(b) Mode M1.)									
2.10 FD bead. Ensure in parking position.									
SMS/80/453/19A					Continued				

SMS 17A

CHAP	5	FLI SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E				
SP NO	506	CONTINUED		Section 1 (1st Edition)				
SHEET	3	AL 12		AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				SERVICING RECORD				
				(1)	(2)	(3)	(4)	(5)
FLI SYST								
2.	<u>Interlock Checks</u> (Contd)							
2.11	PCU.							
	(a)	Stab switch.	Set to 'STAB'.					
	(b)	Supplies M1.	Ensure show Off.					
	(c)	Mode M1.	Note: Mode M1 fitted to Type B PCU is to show Auto.					
2.12	FD bead.							
	Ensure in parking position.							
	Note: Bead is to move to centre if Type B PCU is fitted.							
2.13	PCU.							
	(a)	Master switch.	Set to 'OFF'.					
	(b)	Stab switch.						
2.14	FD/AP switch.							
	(i)	Set to 'OFF'.						
	(ii)	Set to 'AP'.						
2.15	PCU.							
	(a)	Stab switch.	Set to 'STAB'.					
	(b)	Master switch.	Set to 'ON'.					
	(c)	Supplies M1.)	Ensure show Off.					
	(d)	Mode M1.)						
2.16	FD bead.							
	Ensure in parking position.							
2.17	PCU.							
	(a)	Stab switch.)	Set to 'OFF'.					
	(b)	Master switch.)						
2.18	FD/AP switch.							
	Ensure set to 'AP'.							
2.19	PCU.							
	(a)	Master switch.	Set to 'ON'.					
	(b)	Stab switch.	Set to 'STAB'.					
	(c)	Supplies M1.)	Ensure show Off.					
	(d)	Mode M1.)						
2.20	FD bead.							
	Ensure in parking position.							
SMS/80/453/20				Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E				
SP NO	506	CONTINUED		Section 1 (1st Edition)				
SHEET	4	AL 12		AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				SERVICING RECORD				
				(1)	(2)	(3)	(4)	(5)
FLT SYST								
2.	<u>Interlock Checks</u> (Contd)							
2.21	PCU.							
	(a)	Master switch.	} Set to 'OFF'.					
	(b)	Stab switch.						
2.22	FD/AP switch.		Set to 'OFF'.					
2.23	PCU stab switch.		Set to 'STAB'.					
2.24	FD/AP switch.		Set to 'AP'.					
2.25	PCU.							
	(a)	Master switch.	} Set to 'ON'.					
	(b)	Supplies)						
		M1.)						
	(c)	Mode M1.)	Ensure show Off.					
2.26	FD bead.		Ensure in parking position.					
2.27	PCU.							
	(a)	Stab switch.	} Set to 'OFF'.					
	(b)	Master switch.						
2.28	FD/AP switch.		Set to 'OFF'.					
2.29	PCU.							
	(a)	Stab switch.	Set to 'STAB'.					
	(b)	Master switch.	Set to 'ON'.					
2.30	FD/AP switch.		Set to 'AP'.					
2.31	PCU.							
	(a)	Supplies.)	} Ensure show Off.					
		M1.)						
	(b)	Mode M1.)						
2.32	FD bead.		Ensure in parking position.					
2.33	PCU.							
	(a)	Stab switch.)	} Set to 'OFF'.					
	(b)	Master switch.)						
2.34	FD/AP switch.		Set to 'OFF'.					
SMS/453/20A				Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E				
SP NO	506	CONTINUED		Section 1 (1st Edition)				
SHEET	5	AL 12		AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				SERVICING RECORD				
				(1)	(2)	(3)	(4)	(5)
FLT SYST								
2. <u>Interlock Checks</u> (Contd)								
2.35 PCU.								
(a) Master switch.				Set to 'ON'.				
(b) Stab switch.				Set to 'STAB'.				
2.36 FD/AP switch.				Set to 'AP'.				
2.37 PCU.								
(a) Supplies M1.				Ensure shows Black.				
(b) Mode M1.				Ensure shows Auto.				
(c) Attitude switch.				Ensure cannot be cancelled by depressing.				
2.38 FD bead.				Ensure moves to centre of presentation.				
2.39 FD/AP switch.				Set to 'OFF'.				
2.40 PCU glide switch.				Ensure cannot be selected.				
2.41 FD bead.				Ensure moves to parking position.				
2.42 PCU.								
(a) Track switch.				Select.				
(b) Attitude switch.				Ensure cancels.				
(c) Height switch.				Select.				
(d) Track switch.				Ensure cancels.				
2.43 FD/AP switch.				Set to 'AP'.				
SMS/80/453/21				Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E	
SP NO	506	CONTINUED		Section 1	
SHEET	6	AL 12		(1st Edition)	
				AC NO	DATE

Safety and Servicing Notes are to be complied with throughout the work detailed on this card.

			SERVICING RECORD				
			(1)	(2)	(3)	(4)	(5)
FLT SYST							
2.	<u>Interlock Checks</u> (Contd)						
2.44	PCU.						
	(a) Heading switch.	(i) Select. (ii) Cancel.					
	(b) Climb switch.	Ensure cannot be selected by depressing.					
	(c) Attitude switch.						
	(d) Glide switch.						
	(e) Track switch.	Select.					
	(f) Height switch.	Ensure cancels.					
	(g) Climb switch.)	Ensure cannot be selected by depressing.					
	(h) Attitude switch.						
	(j) Height switch.						
	(k) Heading switch.						
	(l) Glide switch.	Select.					
	(m) Track switch.	Ensure remains selected.					
	(n) Climb switch.)	Ensure cannot be selected by depressing.					
	(p) Attitude switch.						
	(q) Height switch.						
	(r) Heading switch.)						
2.45	FD/AP switch.	Set to 'OFF'.					

SMS 17A

SMS/80/453/21A

Continued

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E				
SP NO	506	CONTINUED		Section 1 (1st Edition)				
SHEET	7	AL 12		AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				SERVICING RECORD				
				(1)	(2)	(3)	(4)	(5)
FLT SYST								
2.	<u>Interlock Checks</u> (Contd)							
2.46	PCU.							
	(a)	Glide switch.	Ensure cancelled.					
	(b)	Track switch.	Ensure remains selected.					
	(c)	Heading switch.	Select.					
	(d)	Height switch.	Ensure selects automatically.					
	(e)	Track switch.	Ensure cancels.					
2.47	FD/AP switch.							
2.48	PCU.							
	(a)	Climb switch.) Ensure cannot be selected by depressing.					
	(b)	Attitude switch.						
	(c)	Glide switch.)						
	(d)	Heading switch.	(i) Cancel using keylip.					
			(ii) Reselect.					
	(e)	Mode M1.	Ensure shows 'DIR'.					
	(f)	Master switch.)) Set to 'OFF'.					
	(g)	Stab switch.)						
2.49	FD/AP switch.							
2.50	PCU.							
	(a)	Supplies M1.)) Ensure show Off.					
	(b)	Mode M1.)						
2.51	FD bead.							
3.	<u>Functional Test</u>							
3.1	PCU.							
	(a)	Master switch.	Set to 'ON'.					
	(b)	Stab switch.	Set to 'STAB'.					
	(c)	Attitude switch.	Select.					
3.2	FD/AP switch.							

SMS/80/453/22

Continued

CHAP	5	FLT SYST	SERVICING PROCEDURES		AP101B-1000-5A3 E				
SP NO	506	CONTINUED	LIGHTNING		Section 1 (1st Edition)				
SHEET	8	AL 12			AC NO DATE				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.					SERVICING RECORD				
					(1)	(2)	(3)	(4)	(5)
FLT SYST									
3.	<u>Functional Test</u> (Contd)								
3.3	PCU.								
	(a)	Supplies M1.	Ensure shows Black.						
	(b)	Mode M1.	Ensure shows Auto.						
3.4	FD bead.		Ensure at centre of presentation.						
3.5	'G' test switch.		Set to '3G' position.						
3.6	PCU.								
	(a)	Supplies M1.) Ensure show Off.						
	(b)	Mode M1.)						
3.7	FD bead.		Ensure in parking position.						
3.8	'G' test switch.		Set to 'NORMAL'.						
3.9	PCU.								
	(a)	Stab switch.)	Set to 'OFF'.						
	(b)	Master switch.)							
3.10	FD/AP switch.		Set to 'OFF'.						
3.11	PCU master switch.		Set to 'ON'.						
3.12	Type 8A test set.								
	(a)	Roll rate gyro switch.	Select.						
	(b)	M2 measure switch.	Set to 'RG ROLL'.						
	(c)	Deflect increase switch.	Set to 'MAX'.						
	(d)	Precess rate gyro switch.	Operate.						
	(e)	Meter M2.	Note indication.						
3.13	PCU stab switch.		Set to 'STAB'.						
3.14	Type 8A test set.								
	(a)	Precess rate gyro switch.	Operate.						
	(b)	Meter M2.	Ensure indication decreases from that noted in Sub-item 3.12. Note: Reverse sense indication is acceptable						
SMS/80/453/22A					Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E Section 1 (1st Edition)				
SP NO	506	CONTINUED		AC NO DATE				
SHEET	9	AL 12		SERVICING RECORD				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				(1)	(2)	(3)	(4)	(5)
FLT SYST								
3.	<u>Functional Test</u> (Contd)							
3.15	PCU stab switch.	Set to 'OFF'.						
3.16	Type 8A test set.							
	(a) Yaw rate gyro switch.	Select.						
	(b) M2 measure switch.	Set to 'RG YAW'.						
	(c) Precess rate gyro switch.	Operate.						
	(d) Meter M2.	Note indication.						
3.17	PCU stab switch.	Set to 'STAB'.						
3.18	Type 8A test set.							
	(a) Precess rate gyro switch.	Operate.						
	(b) Meter M2.	Ensure indication decreases from that noted in Sub-item 3.16.						
3.19	PCU Stab switch.	Set to 'OFF'.						
3.20	Type 8A test set.							
	(a) Pitch rate gyro switch.	Select.						
	(b) M2 measure switch.	Set to 'RG PITCH'.						
	(c) Precess rate gyro switch.	Operate.						
	(d) Meter M2.	Note indication.						
3.21	PCU stab switch.	Set to 'STAB'.						
3.22	Type 8A test set.							
	(a) Precess rate gyro switch.	Operate.						
	(b) Meter M2.	Ensure indication reduces from that noted in Sub-item 3.20.						
3.23	Navigation display unit.							
	(a) Compass system.	Ensure synchronized.						
	(b) Select heading pointer.	Set to lubber.						
SMS/80/453/23				Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E			
SP NO	506	CONTINUED		Section 1 (1st Edition)			
SHEET	10	AL 12		AC NO DATE			
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.			SERVICING RECORD				
			(1)	(2)	(3)	(4)	(5)
FLT SYST							
3.	<u>Functional Test</u> (Contd)						
3.24	PCU track switch.	Select.					
3.25	FD/AP switch.	Set to 'AP'.					
3.26	FD bead.	Ensure at centre of presentation.					
3.27	Type 8A test set precess rate gyro switch.	Operate.					
3.28	FD bead.	Ensure moves down.					
3.29	AP trim indicator pointer.	Check indicates Nose Up.					
3.30	FD/AP switch.	Set to 'OFF'.					
3.31	AP trim indicator pointer.	Ensure returns to centre					
3.32	Test socket 'J'.						
	(a) Test lead.	Remove.					
	(b) Blanking plug.	Refit.					
3.33	PCU attitude switch.	Select.					
3.34	FD/AP switch.	Set to 'AP'.					
3.35	4-axis trim indicator tailplane pointer.	Ensure does not move rapidly to fsd.					
3.36	MRG Mk 2 test set Motor Off switch.	Motor off LWL.					
3.37	FD bead.	Ensure moves to right.					
3.38	MRG Mk 2 test set.						
	(a) Motor Off switch.	Release.					
	(b) Erection switch.	(i) Set to 'FAST'.					
		(ii) Set to 'NORMAL'.					
3.39	FD bead.	Ensure returns to centre.					
3.40	PCU BAC.	Rotate anti-clockwise.					
SMS/80/453/23A			Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES		AP101B-1000-5A3 E	
SP NO	506	CONTINUED	LIGHTNING		Section 1 (1st Edition)	
SHEET	11	AL 12			AC NO DATE	
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.					SERVICING RECORD	
					(1)	(2)
FLT SYST						
3. <u>Functional Test (Contd)</u>						
3.41	FD bead.	Ensure moves to left.				
3.42	PCU BAC.	Return to centre.				
3.43	FD bead.	Ensure returns to centre.				
3.44	Tailplane trim switch.	Trim nose down.				
3.45	FD bead.	Ensure moves up.				
3.46	Tailplane trim switch.	Trim to datum.				
3.47	FD bead.	Ensure returns to centre.				
3.48	PCU VSC.	Rotate VSC fully up and leave in position.				
3.49	FD bead.	Ensure moves up then returns to centre.				
3.50	AP trim indicator pointer.	Ensure indicates nose down.				
3.51	Test socket 'J'.					
	(a) Blanking plug.	Remove.				
	(b) Test lead.	Fit.				
3.52	FD/AP switch.	Set to 'OFF'.				
3.53	PCU height and heading switch.	Select.				
3.54	Navigation display unit selected heading pointer.	Ensure aligned with lubber.				
3.55	FD/AP switch.	Set to 'AP'.				
3.56	Navigation display unit selected headings.	Increase by 90 degrees.				
3.57	FD bead.	Ensure moves to right.				
3.58	Navigation display unit selected heading.	Decrease to 10 degrees from lubber.				
SMS/80/453/24					Continued	

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES		AP101B-1000-5A3 E	
SP NO	506	CONTINUED	LIGHTNING		Section 1 (1st Edition)	
SHEET	12	AL 12			AC NO DATE	
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.					SERVICING RECORD	
					(1)	(2)
FLT SYST						
3.	<u>Functional Test</u> (Contd)					
3.59	PCU BAC.	Rotate fully clockwise then release.				
3.60	This Sub-item is applicable only to systems Pre Mod FCS 65.					
	PCU BAC.	Ensure moves to centre.				
3.61	This Sub-item is applicable only to systems Post Mod FCS 65.					
	PCU BAC.	(i) Ensure remains at fully clockwise position. (ii) Return to centre.				
3.62	Navigation display unit selected heading pointer.	Align with lubber mark.				
3.63	MRG Mk 2 test set Motor Off switch.	Motor off to 30 degrees LWL.				
3.64	FS bead.	Ensure moves to right.				
3.65	PCU VSC.	Operate, but not back to detent.				
3.66	FD bead.	Ensure does not move.				
3.67	PCU VSC.	(i) Return to centre detent. (ii) Operate.				
3.68	Attitude indicator.	Ensure follows VSC after movement from detent.				
3.69	MRG Mk 2 test set.	Ensure central.				
	(a) Motor Off switches.					
	(b) Erection switch.	(i) Set to 'FAST'. (ii) Set to 'NORMAL'.				
3.70	FD bead.	Ensure returns to centre.				
3.71	FD/AP switch.	Set to 'OFF'.				
3.72	PCU track switch.	Select.				
3.73	FD/AP switch.	Set to 'AP'.				
3.74	P-S test set.	Increase height gradually				
3.75	FD bead.	Ensure moved down.				
SMS/80/453/24A					Continued	

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES	AP101B-1000-5A3 E	
SP NO	506	CONTINUED	LIGHTNING	Section 1	
SHEET	13	AL 12		(1st Edition)	
			AC NO DATE		
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.			SERVICING RECORD		
			(1)	(2)	(3)
			(4)	(5)	
FLT SYST					
3. <u>Functional Test</u> (Contd)					
3.76	P-S test set.	Restore height to ambient.			
3.77	FD bead.	Ensure returns to centre.			
3.78	P-S test set.	Increase airspeed to 175 kt.			
3.79	Throttles.	Set to mid-position and engage clutch.			
3.80	P-S test set.	Increase airspeed to 185 kt.			
3.81	Throttles.	Ensure move backward.			
3.82	P-S test set.	Decrease airspeed to 165 kt.			
3.83	Throttles.	Ensure move forward.			
3.84	P-S test set.	Restore airspeed to zero kt.			
3.85	Throttles.	Disengage clutch.			
3.86	ILS test set. Type 391.				
	(a) Test set.	Set to 'ON'.			
	(b) Function switch.	Set to 'LOCAL'.			
	(c) Tuning switch.	Set to 'XTAL'.			
3.87	ILS master switch.	Set to 'ON'.			
3.88	ILS channel selector.	Select appropriate channel for test set.			
3.89	ILS test set Type 391.	(i) Adjust deflection until meter indicates zero. (ii) Set maximum right deflection.			
3.90	FD bead.	Ensure moves to right.			
3.91	ILS test set Type 391.	Set deflection to zero.			
3.92	FD bead.	Ensure returns to centre.			
SMS/8C/453/25			Continued		

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES		AP101B-1000-5A3 E		
SP NO	506	CONTINUED	LIGHTNING		Section 1 (1st Edition)		
SHEET	14	AL 12			AC NO DATE		
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.					SERVICING RECORD		
					(1)	(2)	(3)
FLT SYST							
3.	<u>Functional Test</u> (Contd)						
3.93	ILS test set Type 391.						
	(a)	Test set.	Position as near to glide path aerial as possible.				
	(b)	GP aerial.	Extend.				
	(c)	Function switch.	Set to 'GLIDE PATH'.				
	(d)	Test set.	Adjust deflection until meter indicates zero.				
3.94	PCU glide switch.		Select.				
3.95	AP trim indicator pointer.		Ensure indicates nose up				
3.96	ILS test set Type 391.		Set maximum up deflection				
3.97	FD bead.		Ensure moves.				
3.98	ILS test set Type 391.						
	(a)	Test set.	Set deflection to zero.				
	(b)	Function switch.	Set to 'OFF'.				
	(c)	Tuning switch.					
3.99	FD bead.		Ensure returns to centre				
3.100	FD/AP switch.		Set to 'OFF'.				
3.101	PCU climb switch.		Select.				
3.102	AP trim indicator pointer.		Ensure indicates nose down.				
3.103	FD/AP switch.		Set to 'FD'.				
3.104	FD bead.		(i) Ensure moves vertically above centre.				
			(ii) Note position.				
SMS/80/453/25A					Continued		

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES LIGHTNING	AP101B-1000-5A3 E Section 1 (1st Edition)				
SP NO	506	CONTINUED		AC NO DATE				
SHEET	15	AL 12		SERVICING RECORD				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.				(1)	(2)	(3)	(4)	(5)
<p style="text-align: center;">FLT SYST</p> <p>3. <u>Functional Test</u> (Contd)</p> <p>3.105 P-S test set. Increase height at 3000 ft/min to 30000 ft then 45000 ft.</p> <p>3.106 Type 8A test set. (a) 30000 ft lamp. } Ensure light at relevant indicated height. (b) 45000 ft lamp. } </p> <p>3.107 FD bead. Ensure moves down from position noted in Sub-item 3.104.</p> <p>3.108 P-S test set. Restore height to ambient</p> <p>3.109 FD bead. Ensure returns to position noted in Sub-item 3.104.</p> <p>3.110 P-S test set. Increase airspeed slowly to 1.06M.</p> <p>3.111 Type 8A test set. (a) 275 kt lamp. } Ensure light at relevant indicated airspeed. (b) 400 kt lamp. } </p> <p>3.112 FD bead. At 0.89M ensure moves in the vertical plane as Mach number is increased.</p> <p>3.113 P-S test set. Restore airspeed to zero kt.</p> <p>3.114 FD bead. Ensure moves down.</p> <p>3.115 FD/AP switch. Set to 'OFF'.</p> <p>3.116 PCU. (a) Stab switch.) (b) Master switch.) Set to 'OFF'.</p>								
SMS/80/453/26				Continued				

SMS 17A

CHAP	5	FLT SYST	SERVICING PROCEDURES	AP101B-1000-5A3 E				
SP NO	506	CONTINUED	LIGHTNING	Section 1				
SHEET	16	AL 12		(1st Edition)				
Safety and Servicing Notes are to be complied with throughout the work detailed on this card.			AC NO DATE					
			SERVICING RECORD					
			(1)	(2)	(3)	(4)	(5)	
<p style="text-align: center;">FLT SYST</p> <p>4. <u>General</u></p> <p>4.1 MRG On/Off switch.)</p> <p>4.2 Instrument master switch.) Set to 'OFF'.</p> <p>4.3 ILS master switch.)</p> <p>4.4 External power supplies.) (i) Set to 'OFF'.</p> <p>4.5 ILS test set Type 391.) (ii) Disconnect and remove from aircraft.</p> <p>4.6 Type 8A test set.)</p> <p>4.7 MRG Mk 2 test set.) Disconnect and remove from aircraft.</p> <p>4.8 P-S test set.)</p> <p>4.9 Blanking plugs. Refit.</p>								
SMS/80/453/26A								

SMS 17A

This file was downloaded
from the RTFM Library.
Link: www.scottbouch.com/rtfm

Please see site for usage terms,
and more aircraft documents.

