

Internal Checks—*continued*

Front

Ventral tank jettison (F3)	Fully in
Trims	Test each pole for live circuit (first sortie of day). Check trim movement.
	Set: Rudder Neutral
	Aileron Neutral
	Tailplane T/O
Autopilot trim indicator ...	Masked off scale
Flap selector	UP
Flap indicator	Condition
Undercarriage	DOWN
Undercarriage indicator ...	Three green lights. Test alternative bulbs. Day/night as required
Standby artificial horizon	Flag not visible, erect
Brake parachute selector ...	Fully in
Standby altimeter	Set zero
Standby ASI	Needle vertically down
Anti-dazzle lights	OFF
Standby DI	Erect
AAR lights	Out, dimmed as required
Probe light	Off
Emergency lights	Off (check function at night)
LF sight	As required
Hook down light (F6) ...	Press to test. Light out
Hook release handle (F6)	Fully in. Tail of lever in 5 o'clock position
Speed display	Orange disc not visible. Leader spot between reference bars
Altimeter	Orange disc not visible. Set zero. Cross-check with standby
RCDI	Zero
◆ Attitude indicator ...	Erect within 3 minutes of MRG ON. Orange disc not visible ◆

(continued)

This file was downloaded
from the RTFM Library.

Link: www.scottbouch.com/rtfm

Please see site for usage terms,
and more aircraft documents.

