

FUSELAGE
AIR BRAKE SYNCHRONISING JACK

713

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
	-	AIR BRAKE SYNCHRONISING JACK, INSTALLATION (E.B2.00.59)	-	-	-	
26FZ/5542	EEAS.143/6	CLIP, pipe, single, 1/4" o/d Attachments:-	1	L72	C	1/1
28D/9419452	A25/3B	Bolt, 4 BA, hex. head	1	-	C	1/2
28M/1278189	AGS.2001/B/1	Nut, stiff, 4 BA	1	-	C	1/3
28W/9419465	SP13/B	Washer, 4 BA, plain	1	-	C	1/4
5234	E.B2.11.14629	FAIRLEAD, for synchronising shaft	1	LFS26	C	1/5
5235	E.B2.11.14631	FAIRLEAD, for synchronising shaft Attachments:-	1	LFS26	C	1/6
28D/9133012	A25/3C	Bolt, 2 BA, hex. head	2	-	C	1/7
28M/1278190	AGS.2001/C/1	Nut, stiff, 2 BA	2	-	C	1/8
28W/9419402	SP13/C	Washer, 2 BA, plain	2	-	C	1/9
5236	E.B2.11.4977	LEVER, Messier synchronising valve operating, group Spares for:-	1	-	B	1/10
28N/13510	HOFFMANN C.J.O.	BEARING	1	-	C	1/11
28D/1013172	AS.1242/5C	BOLT, 2 BA, c'sk head, lever attachment	1	-	C	1/12
28M/9433473	AGS.2002/C/1	NUT, stiff, 2 BA, lever attachment	1	-	C	1/13
5237	E.B2.11.4981	LEVER, Messier synchronising valve, Teleflex control operating rod connecting, group Spares for:-	1	-	B	1/14
28N/13510	HOFFMANN C.J.O.	BEARING	1	-	C	1/15
28D/1010030	A25/6C	BOLT, 2 BA, hex. head, lever attachment	1	-	B	1/16
28M/9433473	AGS.2002/C/1	NUT, stiff, 2 BA, lever attachment	1	-	C	1/17
28W/91419402	SP13/C	WASHER, 2 BA, plain, lever attachment	1	-	C	1/18
5238	E.B2.11.4993	LEVER, port bellcrank, Teleflex and Messier synchronising rod connecting, group Spares for:-	1	-	B	1/19
28N/13510	HOFFMANN C.J.O.	BEARING	2	-	C	1/20
28M/1011467	A27/ES	TUBE, distance Attachments:-	1	L56	-	
28P/1007741	SP9/C8	Nut, 1/4" BSF, slotted	1	-	C	1/21
28W/9418921	SP13/E	Pin, split	1	-	C	1/22
		Washer, 1/4" BSF, plain	1	-	C	1/23
5239	E.A2.11.4999	LEVER, starboard bell crank, Teleflex and position transmitter operating shaft connecting, group Spares for:-	1	-	C	1/24
28N/13510	HOFFMANN C.J.O.	BEARING	2	-	C	1/25
		TUBE, distance Attachments:-	1	L56	-	
28M/1011467	A27/ES	Nut, 1/4" BSF, slotted	1	-	C	1/26
28P/1007741	SP9/C8	Pin, split	1	-	C	1/27
28W/9418921	SP13/E	Washer, 1/4" BSF, plain	1	-	C	1/28

Restricted

Page H2

**FUSELAGE
AIR BRAKE SYNCHRONISING JACK**

714

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
5240	E.B2.11.7049	LEVER, starboard connecting to position transmitter, air brake and Teleflex control, group (Pre-Mod. 1837) Consisting of:—	1	—	C	1/29
	E.B2.11.7051	LEVER, Teleflex control connecting, group Spares for:—	1	—	—	1/30
28N/13510	HOFFMANN C.J.O.	BEARING	1	—	C	1/31
	E.B2.11.7055	LEVER, position transmitter connecting, group Spares for:—	1	—	—	1/32
28N/13510	HOFFMANN C.J.O.	BEARING	1	—	C	1/33
	E.B2.11.7061	LEVER, air brake connecting, group Spares for:—	1	—	—	1/34
28N/13510	HOFFMANN C.J.O.	BEARING	1	—	C	1/35
28P/16266 12998	SP31/K8 E.B2.11.17953	PIN, taper, lever attachment LEVER, starboard connecting to position transmitter, air brake and Teleflex control, group (Mod. 1837) Spares for this group are identical with those for group Ref. No. 5240	3 1	— —	C C	1/36 1/29A
	E.B2.11.7917	LJNK, starboard, bell crank lever, group Consisting of:—	1	—	C	1/37
5241	E.B2.11.7925	FORK:END, R.H.	1	L65	C	1/38
5243	E.B2.11.7926	FORK:END, L.H.	1	L65	C	1/39
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	—	C	1/40
28M/13454	A27/ETL	NUT, 1/4" BSF, thin, L.H.	1	—	C	1/41
5244	E.B2.11.7911	ROD, screwed, L.H. and R.H.	1	L65	C	1/42
		Attachments:—				
26FZ/220	EEAS.12/1	Bolt, 2 BA, hex. head	2	S11	C	1/43
26FZ/1122	EEAS.63	Nut, 2 BA, slotted	2	S11	C	1/44
28P/1007741	SP9/C8	Pin, split	2	—	C	1/45
28W/9419402	SP13/C	Washer, 2 BA, plain	2	—	C	1/46
28W/9419454	SP10/C	Washer, 2 BA, plain	2	—	C	
	E.B2.11.7919	LJNK, port air brake, group Consisting of:—	1	—	—	1/47
5241	E.B2.11.7925	FORK:END, R.H.	1	L65	C	1/48
5243	E.B2.11.7926	FORK:END, L.H.	1	L65	C	1/49
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	—	C	1/50
28M/13454	A27/ETL	NUT, 1/4" BSF, thin, L.H.	1	—	C	1/51
5245	E.B2.11.7913	ROD, screwed, L.H. and R.H.	1	L65	C	1/52
		Attachments:—				
26FZ/220	EEAS.12/1	Bolt, 2 BA, hex. head	2	S11	C	1/53
26FZ/1122	EEAS.63	Nut, 2 BA, slotted	2	S11	C	1/54
28P/9429528	SP9/C8	Pin, split	2	—	C	1/55
28W/9419402	SP13/C	Washer, 2 BA, plain	2	—	C	1/56
28W/9419454	SP10/C	Washer, 2 BA, plain	2	—	C	

FUSELAGE
AIR BRAKE SYNCHRONISING JACK

115

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
	E.B2.11.7921	LJNK, position transmitter, group Consisting of:-	1	-	-	1/57
5241	E.B2.11.7925	FORK:END, R.H.	1	L65	C	1/58
5243	E.B2.11.7926	FORK:END, L.H.	1	L65	C	1/59
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	-	C	1/60
28M/13454	A27/ETL	NUT, 1/4" BSF, thin, L.H.	1	-	C	1/61
5246	E.B2.11.7915	ROD, screwed, L.H. and R.H.	1	L65	C	1/62
		Attachments:-				
26FZ/220	EEAS.12/1	Bolt, 2 BA, hex. head	2	S11	C	1/63
26FZ/1122	EEAS.63	Nut, 2 BA, slotted	2	S11	C	1/64
28P/1007741	SP9/C8	Pin, split	2	-	C	1/65
28W/9419402	SP13/C	Washer, 2 BA, plain	2	-	C	1/66
28W/9419454	SP10/C	Washer, 2 BA, plain	2	-	C	
	E.B2.11.7923	LJNK, port bell crank lever, group Consisting of:-	1	-	-	1/67
5241	E.B2.11.7925	FORK:END, R.H.	2	L65	C	1/68
28M/13376	A29/EP	NUT, 1/4" BSF, plain	2	-	C	1/69
5247	E.B2.11.7927	ROD, screwed	1	L65	C	1/70
		Attachments:-				
26FZ/220	EEAS.12/1	Bolt, 2 BA, hex. head	2	S11	C	1/71
26FZ/1122	EEAS.63	Nut, 2 BA, slotted	2	S11	C	1/72
28P/1007741	SP9/C8	Pin, split	2	-	C	1/73
28W/9419402	SP13/C	Washer, 2 BA, plain	2	-	C	1/74
28W/9419454	SP10/C	Washer, 2 BA, plain	2	-	C	
	E.B2.11.14889	LJNK, between air brake and synchronising mechanism, group Consisting of:-	1	-	-	1/75
5241	E.B2.11.7925	FORK:END	1	L65	C	1/76
5242	E.B2.11.4887	FORK:END, adjustable	1	L65	C	1/77
28M/13376	A29/EP	NUT, 1/4" BSF, plain	1	-	C	1/78
		Attachments:-				
26FZ/220	EEAS.12/1	Bolt, 2 BA, hex. head	2	S11	C	1/79
26FZ/1122	EEAS.63	Nut, 2 BA, slotted	2	S11	C	1/80
28P/1007741	SP9/C8	Pin, split	2	-	C	1/81
28W/9419402	SP13/C	Washer, 2 BA, plain	2	-	C	1/82
28W/9419454	SP10/C	Washer, 2 BA, plain	2	-	C	
5248	E.B2.11.7433	PIN, special; air brake operating jack connection and anchor	2	S97	C	1/83
		Attachment:-				
28N/2001543	AGS.2031/4	Circlip:	2	-	C	1/84
7247	E.B2.11.16301	PIN, special; air brake operating jack anchor	2	S97	C	1/85
		Attachments:-				
28D/9138768	A25/ 1/2C	Bolt, 2 BA, hex. head	2	-	C	
28W/9419402	SP13/C	Washer, 2 BA, plain	2	-	C	
30A/3055	†	Wire, locking, 22 SWG	QR	-	C	
1484227	E.B2.07.877	STOP, Teleflex control safety (E.B2.11.14545)	1	L72	C	1/86

FUSELAGE
AIR BRAKE SYNCHRONISING JACK

716

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
5250	E.B2.11.7083	TELEFLEX, cable assembly, between synchronising valve and position transmitter on frame 53	1	—	B	1/87
26FZ/220	EEAS.12/1	Attachments:—	2	S11	C	1/88
28D/9436920	A25/1C	Bolt, 2 BA, hex. head	4	—	C	
26FZ/1122	EEAS.63	Bolt, 2 BA, hex. head	2	S11	C	1/89
28M/1278190	AGS.2001/C/1	Nut, 2 BA, slotted	4	—	C	
28P/1007741	SP9/C8	Nut, stiff, 2 BA	2	—	C	1/90
28W/9419454	SP10/C	Pin, split	2	—	C	
28W/9419402	SP13/C	Washer, 2 BA, plain	2	—	C	
		Washer, 2 BA, plain	6	—	C	1/91
	E.B.2.81.10005	TRANSMITTER, position, assembly	1	—	—	1/92
		Consisting of:—				
5251	E.B.2.11.7079	LEVER, transmitter operating, group	1	—	B	1/93
		Spares for:—				
28N/13510	HOFFMANN C.J.O.	BEARING	1	—	C	1/94
		Attachments:—				
28D/9133013	A25/5C	Bolt, 2 BA, hex. head	1	—	C	1/95
28M/9433473	AGS.2002/C/1	Nut, stiff, 2 BA	1	—	C	1/96
28W/9419402	SP13/C	Washer, 2 BA, plain	1	—	C	1/97
6A/4102	SANGAMO WESTON S.132-1-11	TRANSMITTER, position	1	—	A	1/98
		Attachments:—				
28M/9433473	AGS.2002/C/1	Nut, stiff, 2 BA	2	—	C	1/99
26FZ/12292	EEAS.1/7C	Screw, 2 BA, C.sk head, 120 deg.	2	—	C	1/100
	AS.2808/10/041	Tube, distance	1	—	LM	
5252	E.B.2.11.7431	WASHER, special hydraulic, swivel pipes mounting	9	Tufnol ASP sheet	C	1/101

This file was downloaded
from the RTFM Library.

Link: www.scottbouch.com/rtfm

Please see site for usage terms,
and more aircraft documents.

