

MAIN PLANE  
ASSEMBLY OF UNDERCARRIAGE TO STARBOARD WING

1119

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
9962	E.B1.20.2732	BRACKET, fixed fairing to main undercarriage leg attachment, inboard centre position, group Spares for:—	1	—	C	4B/253
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	—	C	4B/48
2973	E.B1.20.2743	SCREW, adjusting	1	—	C	4B/49
22504	E.B1.20.2715	WASHER, special, belville	2	DTD187A or 271	C	4B/50
28D/9133012	A25/3C	Attachments:— Bolt; 2:BA, hex. head	6	—	C	4B/51
9963	E.B1.20.2737	BRACKET, fixed fairing to main undercarriage leg attachment, inboard rear position, assembly Spares for:—	1	—	C	4B/52
22504	E.B1.20.2715	WASHER, special, belville	2	DTD187A or 271	C	4B/53
28D/9133012	A25/3C	Attachments:— Bolt; 2:BA, hex. head	4	—	C	4B/54
9964	E.B1.20.2745	BRACKET, fixed fairing to main undercarriage leg attachment, outboard rear position, assembly Spares for:—	1	—	C	4B/55
22504	E.B1.20.2715	WASHER, special, belville	2	DTD187A or 271	C	4B/56
28D/9133012	A25/3C	Attachments:— Bolt; 2:BA, hex. head	4	—	C	4B/57
9965	E.B1.20.2750	BRACKET, fixed fairing to main undercarriage leg attachment, outboard centre position, assembly Spares for:—	1	—	C	4B/254
22504	E.B1.20.2715	WASHER, special, belville	2	DTD187A or 271	C	4B/59
28D/9133012	A25/3C	Attachments:— Bolt; 2:BA, hex. head	2	—	C	4B/60
28D/1200119	A25/4C	Bolt; 2:BA, hex. head	1	—	C	4B/61
12530	E.B2.81.8072	BRACKET, mounting	1	L72	C	
12529	E.B2.81.8066	BRACKET, nut	1	—	C	
12528	E.B2.20.8426	FAIRING, taxiing lamp	1	—	C	4B/256
	E.B2.20.6470	PACKING, main undercarriage aft hinge fairing	1	L72	—	
12525	E.B1.20.3107	PLATE, service	4	DTD546	C	4B/70
33734	E.B2.20.6988	PLATE, service	1	L73	C	4B/258
33733	E.B1.20.3112	PLATE, service	1	DTD546	C	4B/257
12508	E.B1.20.8405	WASHER, special, fairing bracket attachment	9	L73	C	4B/73
12509	E.B1.20.8407	WASHER, special, fairing bracket attachment	9	S510 or S92	C	4B/74
12510	E.B1.20.8409	WASHER, special, fairing bracket attachment	2	S510 or S92	C	4B/75
30	E.B3.20.54	FAIRING, hinged, forward, main undercarriage, group Spares for:—	1	—	A	4B/259
13750	E.B2.07.614	BRACKET, catch 'up' lock (E.B1.20.2896)	1	DTD721	C	4B/260

ASSEMBLY ORDER OF CONFERENCE - 25th GARD W...

111

Line No.	Description	Quantity	Unit Price	Total Price
101	...	...	...	...
102	...	...	...	...
103	...	...	...	...
104	...	...	...	...
105	...	...	...	...
106	...	...	...	...
107	...	...	...	...
108	...	...	...	...
109	...	...	...	...
110	...	...	...	...
111	...	...	...	...
112	...	...	...	...
113	...	...	...	...
114	...	...	...	...
115	...	...	...	...
116	...	...	...	...
117	...	...	...	...
118	...	...	...	...
119	...	...	...	...
120	...	...	...	...
121	...	...	...	...
122	...	...	...	...
123	...	...	...	...
124	...	...	...	...
125	...	...	...	...
126	...	...	...	...
127	...	...	...	...
128	...	...	...	...
129	...	...	...	...
130	...	...	...	...
131	...	...	...	...
132	...	...	...	...
133	...	...	...	...
134	...	...	...	...
135	...	...	...	...
136	...	...	...	...
137	...	...	...	...
138	...	...	...	...
139	...	...	...	...
140	...	...	...	...
141	...	...	...	...
142	...	...	...	...
143	...	...	...	...
144	...	...	...	...
145	...	...	...	...
146	...	...	...	...
147	...	...	...	...
148	...	...	...	...
149	...	...	...	...
150	...	...	...	...

**This page JE4 was blank in the original apparently genuine copy, perhaps as a printing error.**

MAIN PLANE  
ASSEMBLY OF UNDERCARRIAGE TO STARBOARD WING

1121

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
28N/13511	HOFFMANN CJ.1	JOINT, self-aligning	1	—	C	4A/114
3139	E.B1.20.1910	LINK, connecting, between trigger mechanism and hook, c/w bush	1	—	C	4A/267
3140	E.B1.20.1908	MECHANISM, trigger, assembly Spares for:—	1	—	B	4A/268
12517	E.B1.20.1965	BOLT, adjusting, lower	1	—	C	4A/117
12518	E.B1.20.1967	BOLT, adjusting, upper	1	—	C	4A/118
25159	E.B1.20.1969	STOP, segment	1	S96	C	4A/119
28N/9156370	SP21	NIPPLE, grease, for hook pivot bolt	1	—	C	4A/120
28M/1011467	A27/ES	NUT, 1/4" BSF, slotted, for trigger mechanism and connecting link	2	—	C	4A/121
28M/1006473	A27/CT	NUT, 2 BA, thin, hook limit stop adjusting bolt	1	—	C	
28M/1278190	AGS.2001/C/1	NUT, 2 BA, stiff, keep-plates and stop fixing bolts	4	—	C	4A/122
10764	E.B2.20.8901	NUT, special, 2 BA	1	S113	C	4A/123
10786	E.B2.20.9215	NUT, special	1	—	C	4A/124
2992	E.B1.20.1915	PIECE, distance, shouldered, keep-plates retaining	2	L65	C	4A/125
2993	E.B1.20.1917	PIECE, distance, plain between keep-plates	3	L65	C	4A/126
2994	E.B1.20.7621	PIECE, distance, for keep-plates at hook limit stop	1	L62	C	4A/127
2995	E.B1.20.1931	PiN, special, lower spring barrel attachment to trigger mechanism	1	S96	C	4A/128
34478	E.B3.20.1945	PiN, toggle, trigger mechanism and hook connecting link	1	S96	C	4A/129
28P/1007741	SP9/C8	PiN, split, 1/16" dia. x 1" long, trigger mechanism pivot bolt and connecting link nuts retaining	2	—	C	4A/130
28P/1007740	SP9/B4	PiN, split, 3/64" dia. x 1/2" long, for lower spring barrel attachment pin	1	—	C	4A/131
2997	E.B1.20.1919	PLATE, locking, trigger mechanism and hook pivot bolts	2	L65	C	4A/132
28S/1011501	A33/C6	SCREW, 2 BA, c'sk head, locking plate securing	2	—	C	4A/133
2998	E.B1.20.7617	STOP, hook limit	1	L65	C	4A/134
2999	AUT'VE ENG.	TWICLIP, 5/16" BSF, toggle pin retaining	1	—	C	4A/135
3000	AUT'VE ENG.	TWICLIP, 7/16" BSF, main pivot bolt retaining	1	—	C	4A/136
28W/9419475	SP15/C	WASHER, 2 BA, plain, for lower spring barrel attachment pin	1	—	C	4A/137
28D/1212387	A25/14G	Attachments:— Bolt, 5/16" BSF, hex. head	3	—	C	4A/138
28M/10291	AGS.2001/G/1	Nut, 5/16" BSF, stiff	3	—	C	4A/139
3001	E.B1.20.2269	LATCH, undercarriage door, c/w bushes	1	—	C	4/140
35328	E.F3.20.4048	LINK, actuating, aft flap, group (Mod. 2391) Spares for:—	1	—	C	4B/269
17693	E.B2.20.8937	PiN	1	S96	C	4B/142
22500	E.B4.20.9429	PiN, aft flap actuating link	1	S96	C	4B/143
2979	E.B2.20.9355	LINK, actuating, forward flap, group Spares for:—	1	—	C	4C/144
	E.B2.20.3815	TUBE, assembly Spares for:—	1	—	—	4C/145
29723	E.B2.20.7777	BOLT, special	2	S96	C	4C/146

MAIN PLANE  
ASSEMBLY OF UNDERCARRIAGE TO STARBOARD WING

112.

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
3002	E.B1.20.2169	LINK, connecting, undercarriage door aft end : latches, group : Spares for:—	1	—	B	4/147
3003	E.B1.20.2173	CONNECTOR, adjustable, c/w bush, group : Spares for:—	1	—	C	4/148
3004	E.B1.20.2461	NUT, special lock (Make from A27QT or S96)	1	—	C	4/149
3005	E.B1.20.2255	LINK, drag, between latch mechanism and bell- : crank lever, group : Consisting of:—	1	—	B	
3006	E.B1.20.2253	BOLT, bell-crank lever connecting	1	S96	C	4/150
3007	E.B1.20.2261	BOLT, special, latch connecting	1	S96	C	4/151
28N/13511	HOFFMANN CJ.1	JOINT, self-aligning	1	—	C	4/152
28M/5808573	E.B1.20.2257	LINK, drag	1	L65	—	4/153
	A27/CS	NUT, 2 BA, slotted	2	—	C	4/154
28P/1007741	E.B1.20.2259	PIECE, distance, at latch end	2	L65	—	4/155
	E.B1.20.2295	PIECE, distance, at fork end	2	L65	—	4/156
28W/9419405	SP9/C8	PIN, split, 1/16" dia. x 1" long	2	—	C	4/157
1441421	SP15/E	WASHER, 1/4" BSF, plain	3	—	C	4/158
3009	E.B2.20.9515	LINK, tubular, for bell-crank, group (Mod. 4211) : Consisting of:—	1	—	C	4A/159
	E.B1.20.2283	BOLT, special, 2 BA	2	S96	C	4A/160
3004	E.B1.20.2461	NUT, lock	1	S94 or S96	C	4A/161
28M/5808573	A27/CS	NUT, 2 BA, slotted	2	—	C	4A/162
28P/1007741	SP9/C8	PIN, split	2	—	C	4A/163
1441423	E.B2.20.9517	TUBE, assembly : Spares for:—	1	—	—	4A/164
	E.B2.20.9513	COLLAR, spring retaining	1	L64	C	
1441424	E.B1.20.2277	SLEEVE, screwed	1	L65	—	
	E.F3.20.4279	SLEEVE, protection	1	T55 or S521	C	
28W/9471273	E.B1.20.2275	TUBE, .20 SWG	1	T4	—	
	SP124/E	WASHER, 1/4" UNF, packing	2	—	C	4A/165
12515	E.B1.20.2281	YDKE-END, screwed	1	L65	C	4A/166
26FZ/1195	EEAS.37/14A	Attachments:— Nipple, 4 BA	4	S96	C	4A/167
	AGS.2050/624BS	Rivet, tucker, 3/16" dia., domed head	2	—	C	
28Q/9417277	EEAS.38/2A	Spoke, 4 BA (Make from 28R/6124)	2	S94, S95 or S96	LM	4A/169
	1441425	E.F3.20.4271	Spring, compression	1	DTD215 or 239	C
3010	E.B1.20.2289	LINK, forked, bell-crank connection, master latch : end, group : Consisting of:—	1	—	B	4A/171
3011	E.B1.20.2293	BOLT, special	2	S96	C	4A/172
	E.B1.20.2291	LINK, forked	1	L65	—	4A/173
28M/5808573	A27/CS	NUT, 2 BA, slotted	2	—	C	4A/174
	E.B1.20.2295	PIECE, distance	4	L65	—	4A/175
28P/1007741	SP9/C8	PIN, split, 1/16" dia. x 1" long	2	—	C	4A/176
28W/9419405	SP15/E	WASHER, 1/4" BSF, plain	2	—	C	4A/177
3201	E.B1.20.1900	MECHANISM, main undercarriage door micro-switch, : group : Spares for:—	1	—	A	4A/270
28D/9130080	AS.1242/9B	BOLT, 4 BA, c'sk head, micro-switch mounting	2	—	C	4/179

MAIN PLANE  
ASSEMBLY OF UNDERCARRIAGE TO STARBOARD WING

1123

Ref. No.	Part No.	Description	No. off	Matl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
3014	E.B1.20.2619	HOUSING, plunger, group Spares for:—	1	—	C	4/180
	E.B1.20.2627	BUSH	1	DTD412	—	
3202	E.B2.20.9030	LATCH, undercarriage door 'up', group Consisting of:—	1	—	B	4/271
3006	E.B1.20.2253	BOLT, special, mechanism control connecting	1	S96	C	4/182
	E.B1.20.2467	BUSH, main pivot	2	DTD412	—	4/183
29795	E.B2.20.8716	HOOK	1	S96	C	4/272
	or					
	E.B2.20.8718					
28M/5808573	A27/CS	NUT, 2 BA, slotted	1	—	C	4/185
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	—	C	4/186
10766	E.B2.20.8995	PIN, locating	1	S96	C	4/187
28P/1006943	SP9/C6	PIN, split	1	—	C	4/188
28W/9418921	SP13/E	WASHER, 1/4" BSF, plain	1	—	C	4/189
3018	E.B1.20.2629	LEVER, door trip, group Spares for:—	1	—	B	4/190
2A/9500409	SKEFCO CBS 0	BEARING	1	—	C	4/191
28D/1200119	A25/4C	BOLT, 2 BA, hex. head	1	—	C	4/192
28M/5808573	A27/CS	NUT, 2 BA, slotted	1	—	C	4/193
28P/1007741	SP9/C8	PIN, split, 1/16" dia. x 1" long	1	—	C	4/194
3019	E.B1.20.3403	LEVER, trip	1	L65	C	4/195
3020	E.B1.20.8295	LINK, plunger	1	L65	C	4/196
3021	E.B1.20.2633	LINK-PLATE, for bell-crank	2	DTD546	C	4/197
3022	E.B1.20.8291	LINK-PLATE, for trigger, L.H.	1	L65	C	4/198
3023	E.B1.20.8292	LINK-PLATE, for trigger, R.H.	1	L65	C	4/199
3024	E.B1.20.8285	LINK-PLATE, mechanism travel	1	L65	C	4/200
28F/9156370	SP21	NIPPLE, grease	1	—	C	4/201
3025	E.B1.20.8289	NUT, special, trunnion, for travel adjustment	1	S96	C	4/202
28M/1278190	AGS.2001/C/1	NUT, stiff, 2 BA, plunger housing and keep-plate retaining screw	7	—	C	4/203
28M/1278189	AGS.2001/B/1	NUT, stiff, 4 BA, for micro-switch mounting bolt	2	—	C	4/204
28M/1007403	A27/ET	NUT, 1/4" BSF, thin	1	—	C	4/205
3026	E.B1.20.2647	PIECE, distance, shouldered, between keep-plates	2	L65	C	4/206
3027	E.B1.20.2649	PIECE, distance, plain, for keep-plates	3	L65	C	4/207
3028	E.B1.20.2651	PIECE, distance, for trip lever	2	L65	C	4/208
3029	E.B1.20.2653	PIECE, distance, shouldered, for latch pivot	1	S96	C	4/209
3030	E.B1.20.2631	PIN, door trip lever and trigger pivot	2	S96	C	4/210
3031	E.B1.20.2635	PIN, link, long	2	S96	C	4/211
3032	E.B1.20.2637	PIN, link, short	1	S96	C	4/212
3033	E.B1.20.2641	PIN, plunger guide	1	S96	C	4/213
3034	E.B1.20.3407	PIN, trip lever pivot	1	S96	C	4/214
28P/1007741	SP9/C8	PIN, split, 1/16" dia. x 1" long, link washer retaining	6	—	C	4/215
3036	E.B1.20.2621	PLUG, plunger spring retaining	1	L65	C	4/217
3035	E.B1.20.2625	PLUNGER, micro-switch operating	1	S11	C	4/216
3037	E.B1.20.8267	ROD, mechanism travel adjustment	1	—	C	4/218
3038	EEAS.1/9C	SCREW, 2 BA, 120 deg. c'sk head, plunger housing and keep-plate retaining	7	S96	C	4/219
3039	E.B1.20.2623	SPRING, compression, plunger loading 16 SWG x 3".63 free length	1	Spring Wire	C	4/220
5378	E.B1.20.8365	SPRING, torsion, for trip lever, 26 SWG	1	DTD215 or 239	C	4/221

MAIN PLANE  
ASSEMBLY OF UNDERCARRIAGE TO STARBOARD WING

112

Ref. No.	Part No.	Description	No. off							Mtl. Spec.	Cl. of Equip. M.R. L.M.	Fig. and Index
			1	2	3	4	5	6	7			
5CW/10969	†	SWITCH, limit							1	—	B	4/222
3041	E.B1.20.8283	TRIGGER							1	S96	C	4/223
3042	E.B1.20.8287	TUBE, trunnion nut clamping							1	S96	C	4/224
28W/9419402	SP13/C	WASHER, 2 BA, plain, for link lever							6	—	C	4/226
3043	E.B1.20.8293	WASHER, link spacing							2	L65	C	4/225
28N/9156370	SP21	NIPPLE, grease							3	—	C	4/227
5275	E.B1.20.2747	PIECE, distance, for undercarriage door latch							2	L65	C	4/228
3044	E.B1.20.5091	PIN, hinge, main undercarriage door centre							1	S96	C	4/229
4878	E.B2.20.6229	PN, pivot, main undercarriage door latch bell-crank							1	S96	C	4/230
		Attachments:—										
28D/9133011	A25/2C	Bolt, 2 BA, hex. head							3	—	C	4/231
28M/5808573	A27/CS	Nut, 2 BA, slotted							3	—	C	4/232
28M/1011467	A27/ES	Nut, 1/4" BSF, slotted							1	—	C	
28P/1006943	SP9/C6	Pin, split, 1/16" dia. x 1" long							3	—	C	4/233
28W/9419402	SP13/C	Washer, 2 BA, thin							3	—	C	4/234
28W/9418921	SP13/E	Washer, 1/4" BSF, thin							1	—	C	
5276	E.B1.20.7575	PIN, pivot, main undercarriage door latch bell-crank, c/w grease nipple							1	S96	C	4/235
		Attachments:—										
28D/1214091	AS.1242/2C	Bolt, 2 BA, c'sk head							1	—	C	4/236
5274	E.B1.20.7587	Stop, 1/2 SWG							1	L72	C	4/237
3048	E.B1.20.7583	PIN, pivot, for main undercarriage door 'up' latch jack							1	S96	C	
35	E.B1.20.1481	SHAFT, main undercarriage pivot							1	S99	C	4/239
3049	E.B2.20.1587	SHIM, for master latch							3	Laminated Alum.	C	4/240
8986	E.B2.20.8903	SHIM, undercarriage door stop							QR	Laminated Alum.	C	
5264	E.B1.20.5566	TAB, locking, for main undercarriage door hinge pin							1	DTD546	C	4/273
		Attachments:—										
26FZ/5842	EEAS.134/2C	Bolt, 2 BA, 90 deg. c'sk head							1	S97	C	4/243
28M/5808573	A27/CS	Nut, 2 BA, slotted							1	—	C	4/244
28P/1007741	SP9/C8	Pin, split, 1/16" dia. x 1" long							1	—	C	4/245
5272	E.B1.20.7111	TUBE, bearing, for main undercarriage door inboard hinge							1	DTD625	C	4/246
3052	E.B1.20.5567	WASHER, spacing, for main undercarriage 'up' lock linkage bell-crank							2	L65	C	4/247

This file was downloaded  
from the RTFM Library.

Link: [www.scottbouch.com/rtfm](http://www.scottbouch.com/rtfm)

Please see site for usage terms,  
and more aircraft documents.

