

PART II
LIMITATIONS

LIST OF CHAPTERS

	Chapter
Engine limitations 1
Airframe and miscellaneous limitations 2

PART II—LIMITATIONS

Chapter 1—ENGINE LIMITATIONS

Contents

Engine limitations—Avon Mk. 109	Para. 1
Oil limitations	2
Fuel and oil specifications	3

1 Engine limitations—Avon Mk. 109

Power rating	Time limit per flight	RPM	JPT °C
Max. take-off and operational necessity	10 mins.	7,950 ± 50	680
Max. intermediate	30 mins.	7,750	620
Max. continuous	Unrestricted	7,500	575
Idling on ground	Unrestricted	2,750 ± 100	530

NOTE 1: At low air temperatures the engines may underspeed to as low as 7,800 RPM at full throttle but they will still maintain maximum thrust.

NOTE 2: The ground RPM will vary with a change in fuel density from that at which the engine settings were made. A higher density will cause a drop in RPM and a lower density a rise. Every 0.01 change in density will cause a corresponding difference of 50 in the ground RPM.

2 Oil limitations

Oil pressures

Minimum at 7,500 RPM and above ...	15 PSI
Normal at 7,500 RPM	20 PSI
Minimum at idling RPM... ..	3 PSI

3 Fuel and oil specifications

The engines are cleared for the following fuels and oils provided that the engines are adjusted as laid down in AP.4321 J, U and V, Vol. 1.

<i>Fuel</i>	<i>Reference No.</i>	NATO <i>Code No.</i>
AVTUR/50	34A/9431771	F.35
AVTUR/50 with icing inhibitor	34A/2201036	F.34
AVTAG	34A/9100448	F.45
AVTAG with icing inhibitor	34A/2201037	F.40
◀AVCAT	—	F.44 ▶
<i>Oil</i>	<i>Reference No.</i>	<i>Code No.</i>
OX-38	34A/9100591	0-149

PART II—LIMITATIONS

Chapter 2—AIRFRAME AND MISCELLANEOUS LIMITATIONS

Contents

	Para.
General	1
Speed and mach number limitations	2
Maximum weights	3
cg limits (feet aft of datum)	4
Manoeuvre limitations	5
Jettisoning of wing-tip tanks	6
Armament limitations	7
Aircraft approach limitations	8
Ejection seat	9
Barrier engagement	10

1 General

The Canberra B(I) Mk. 8 is designed as a light bomber/interdictor and is cleared for normal bombing and loft bombing. Intentional spinning and aerobatics, other than the loft bombing manoeuvre, are prohibited.

2 Speed and mach number limitations

	Condition	Max. IAS	Max. IMN
(a)	Airframe limitations Clean	450	0.75M below 15,000 ft. 0.79M 15,000 to 25,000 ft. Above 25,000 ft. limited by compressibility effects. The speed at which a nose-up change of trim occurs i.e. about 0.84M, must not be exceeded.
(b)	With wing-tip tanks	365	0.79M below 25,000 ft. 0.80M above 25,000 ft.

	Condition	Max. IAS	Max. IMN
(c)	With rockets	As at (a) and (b) above	
(d)	For the operation of: Bomb/flare doors (See note 2)	350	0.75M up to 40,000 ft. 0.80M above 40,000 ft.
	Airbrakes MID	No limit	No limit
	Airbrakes OUT	400	0.75M, 12,500 to 25,000 ft. 0.79M above 25,000 ft.
	Undercarriage	190	
	Flaps	160	

NOTE 1: The speed for the operation of a service also applies for flight with the service in the extended position.

NOTE 2: When the deflector is installed in the bomb-bay the bomb doors may be opened at speeds up to 450 kts., depending on the type of store carried. Full details are given in the "Release to Service".

3 Maximum weights

For take-off and all permitted forms of flying 56,750 lb.
 Max. normal for landing 40,000 lb.

NOTE: In emergency the aircraft may be landed at higher weights but greater care will be required particularly when braking (see Part III, Ch. 3, para. 5).

4 CG limits (feet aft of datum)

(a) In flight and landing

(i) Forward limit with or without tip tanks

1.235 ft. aft up to 29,000 lb. then varying linearly aft
 to 2.200 ft. aft at 48,000 lb., remaining constant there-
 after at 2.200 ft. up to maximum take-off weight.

(ii) Aft limit

Without wing tip tanks 3.058 ft. aft
 With wing tip tanks 2.810 ft. aft

(b) When taxiing over uneven surfaces the aft limit should not exceed 2.885 ft.

5 Manoeuvre limitations

Combined application of coarse aileron and "G" should be avoided.

The acceleration limitations are as follows:—

*(a) At weights up to 48,000 lb. without tip-tanks**(i) With negligible aileron applied*

Integral tanks full	4.0G
-----------------------------	------

Integral tanks less than full	3.5G
---------------------------------------	------

(ii) With aileron applied

Integral tanks full	3.5G
-----------------------------	------

Integral tanks less than full	2.0G
---------------------------------------	------

(b) At weights above 48,000 lb. or with wing-tip tanks fitted

(i) With negligible aileron applied	3.0G
---	------

(ii) With aileron applied	1.5G
-----------------------------------	------

*(c) Rocket firing (37 × 2 in. rocket launchers) 40,000 lb. AUW (max.)**(i) With airbrakes retracted or in MID position*

Below 0.75M or 450 Kts.	3.0G
---------------------------------	------

From 0.75M to 0.83M or 450 Kts.	2.0G
---	------

(ii) With airbrakes fully out

Below 0.75M or 400 Kts.	3.0G
---------------------------------	------

From 0.75M to 0.79M or 400 Kts.	2.0G
---	------

These limitations apply during the actual firing only.

NOTE: The aircraft is released for the interdicator role subject to the conditions stated and bearing in mind that the strength factors of the Canberra are lower than those normally required for a pure ground attack aircraft.

6 Jettisoning of wing-tip tanks

The wing-tip tanks may be jettisoned at any speed, full or empty, within the limitations imposed when carrying wing-tip tanks.

7 Armament limitations

When carrying armament stores, there may be certain limitations imposed additional to those quoted above. It

is essential, therefore, that if any armament stores are carried, any limitations associated with their carriage and release or jettisoning are obtained from the "Release to Service" before flight.

8 Aircraft approach limitations

The following are the normal aircraft approach limitations:—

GCA (Precision)	200 ft.
ILS (Raw)	300 ft.
ILS—Zero reader	200 ft.

9 Ejection seat Type 2CB

Ejection may be initiated, in straight and level flight, at any height from ground level upwards. However, runway ejections should only be made when the speed of the aircraft is above 90 kts. or the circumstances of the emergency dictate that ejection is the only reasonable solution. If at any time the aircraft is nose-down or descending, the minimum safe height is increased and depends on the angle of dive and aircraft speed.

10 Barrier engagement

The Canberra B(I) Mk. 8 is cleared for engagement with the Mk. 6 and Mk. 12 arrester barriers. When engaging the Mk. 12 barrier, only one braking drum of the barrier should be connected.

This file was downloaded
from the RTFM Library.

Link: www.scottbouch.com/rtfm

Please see site for usage terms,
and more aircraft documents.

