

## Chapter 2

### DUPLEX DROGUE AND APRON

#### Servicing note

1. The operations detailed in this schedule are to be done by a Safety Equipment Worker.

Item No.	Item	Operation
1	Complete assembly	(1) Examine for dampness and, if necessary, hang until thoroughly dry. (2) Lay out on a parachute table.
2	Drogues (22 in. and 5 ft.)	Examine canopies for deterioration, defective stitching, holes, tears and damage.
3	(a) Shroud lines (b) Nylon rope (c) Lifting lines (d) Withdrawal line	(1) Examine for deterioration, fraying and damage. (2) Examine all whipping and adhesive tape for security and damage. (3) Examine the black P.V.C. covering on lifting lines for deterioration and damage. (4) Examine the metal lugs and securing pins for distortion and damage.
4	5 ft. withdrawal line	Examine for deterioration, fraying and security of attachment to the apex of the 5 ft. drogue and to the whipping on the base of the 22 in. drogue shroud lines.
5	Slide disconnect fitting	Examine for distortion and damage.
6	Headrest and apron	(1) Examine for broken stitching, deterioration, holes and damage. (2) Examine metal fittings for distortion, damage and security of attachment.
7	(a) Drogue shackle (b) Drogue gun shackle (c) Quick-release and flap securing pins	Examine for distortion and damage.
8	Servicing record slips	Sign for completing this servicing.

This file was downloaded  
from the RTFM Library.

Link: [www.scottbouch.com/rtfm](http://www.scottbouch.com/rtfm)

Please see site for usage terms,  
and more aircraft documents.

