# Chapter 94 RELAY, PLESSEY, TYPE 7CZ/97225/I

## LIST OF CONTENTS

			Para.				Para.
Introduction	 	 	 1	Description	 	 	 2

# LIST OF ILLUSTRATIONS

			Fig.
Circuit diagram	 	 •••	 1

### LEADING PARTICULARS

Relay, Type 7CZ/972	 	 Stores Ref. 5CW			
Operating voltage		 	 16 to 29 volts d.c.		
Contact rating		 	 30 amp at 28 volts d.c.		
Coil resistance	•••	 	 250 ohms $\pm$ 5 per cent		
Overall dimensions	•••	 	 3 in. $ imes$ 1 in. $ imes$ 2·5 in		
Weight		 	 5 <sup>3</sup> / <sub>4</sub> oz		

### Introduction

1. The relay, Type 7CZ/97225/1, is a single-pole, normally-open sealed relay for use on aircraft where the current does not exceed 30 amp.




Fig. I. Circuit diagram

# DESCRIPTION

- 2. A circuit diagram of the relay is given in fig. 1. The mechanism incorporates an electro-magnet mounted centrally on the base; when the coil is energized, the armature is attracted to the core to close the contacts.
- **3.** Electrical connection to the coil and the contacts is made to screw type terminals, 6 B.A. for the coil and 4 B.A. for the contacts. Two mounting flanges are provided, each with a single fixing hole.