Chapter 50

BULKHEAD LAMPS, THORN, TYPE 80/10/1032 and 80/10/0610

LIST OF CONTENTS

			I	Para.
Introduction	•••		 	1
Description		• • •	 	2
Servicing			 	6

LIST OF ILLUSTRATIONS

					Fig.
External view	of a t	ypical la	mp		1
Type 80/10/10)32 la	mp with	cover	re-	
moved					2

LEADING PARTICULARS

Bulkhead l	amp, Thor	n, Type	80/10	1032	• • •		Ref. N	o. 5CX/5444
Bulkhead l	amp, Thor	п, Туре	80/10	0610			Ref. N	o. 5CX/5949
Rating								
Type	80/10/103	2 lamp,	fitted	with o	a maxin	num	of 24	
u	vatts						•••	Continuous
Туре	80/10/0610	lamp,	fitted	with a	a maxin	num	of 19	
T.C	atts							Continuous




Fig. 1. External view of a typical lamp

Introduction

1. ◆The Thorn, Type 80/10/1032 and Type 80/10/0610 bulkhead, or flood, lamps are used for general illumination in aircraft cabins, freight holds, and passenger compartments. The Type 80/10/1032 lamp is a twin-filament version of the lamp suitable for use in red/white lighting systems, and is the lamp described and illustrated in this chapter. The Type 80/10/0610 lamp is a single-filament version of the lamp, identical in other respects to the twin-filament version. ▶

DESCRIPTION

2. The lamp consists of two parts: the base and the cover. The base, shown in Fig. 2, is a

light alloy stamping recessed towards one end to form a shallow bowl. This bowl forms the reflector. Two single centre contact lampholders are mounted horizontally on the base, and held in position by two clips riveted to the base. Each lampholder is positioned by a spring-loaded spigot contained in the lampholder, and clamped by a nut and bolt tightened against a collar between the faces of the clip.

- 3. A bushed hole in the base of the lamp between the lampholders provides access for the cable. The positive supply is connected to the screw terminals at the rear of the lampholders, and the negative return is connected to one of clamping screws. Four spaced holes in the outer edge of the reflector bowl are provided for fixing the base to its required position. Two phosphor bronze springs riveted at either end of the base keeps the cover under tension, and prevents it from vibrating when it is in position.
- 4. The cover consists of a light alloy rim containing a white plastic light diffuser, the light diffuser being held in position by a metal band riveted on the inside of the rim. Two snap locks, secured to the rim, locate in the two holes provided in the base and retain the cover in position.
- 5. Light is provided by two S.C.C. filament lamps, one clear and the other red. These lamps can be wired to a suitable switch for alternate switching if required. By applying pressure on the two finger buttons the cover can be removed, giving access to filament lamps and terminal connections.

PLASTICS LIGHT DIFFUSER PHOSPHOR-BRONZE SPRINGS BASE AND REFLECTOR

Fig. 2. Type 80/10/1032 lamp with cover removed

SERVICING

6. Servicing of these lamps will normally be confined to the renewal of the filament lamps, the cover, or complete units. For lamps in continuous use (passenger compartments, galley etc.) care must be taken to ensure that the maximum wattage of the filament lamps used does not exceed 24 watts for the Type 80/10/1032, and 19 watts for the Type 80/10/0610. ▶