

# PART IV EMERGENCIES

# LIST OF CHAPTERS

Malfunctioning and emergency procedures ... 1





D .....

## PART IV -- EMERGENCIES

# Chapter 1 — MALFUNCTIONING AND EMERGENCY PROCEDURES

#### Contents

General .						1
Considerations	when	abando	oning			2
Considerations	when	using t	he airfield	arrester	barrier	3

#### 1 General

FS1

All system malfunctioning drills and emergency handling drills are in the Flight Reference Cards but consideration of certain emergency techniques is covered in paras 2 to 4 of this chapter. In addition, the malfunctioning of the various systems is covered in the appropriate chapters of this book as shown in the following index.

	Pt. Ch.	para.
FAILURES	I, 1,	16
ENGINE FAILURES		
Engine failure during take-off Engine failure after take-off Engine failure in flight (clean) Engine failure in approach con-	III, 1, III, 1, III, 2,	9 10 17
figuration (blown) IGV failures	III, 3, I, 5,	11 22
FUEL FAILURES		
Contents indicator failure Single proportioner failure Double proportioner failure Rebalancing	I, 2, I, 2, I, 2, I, 2, I, 2,	29 31 32 30
FUEL JETTISON	I, 2,	28
HYDRAULIC FAILURES, FLY- ING CONTROLS SYSTEM Single system failure Double system failure	I, 3, I, 3,	14 15

HYDRAULIC FAILUR GENERAL SERVICE SYSTEM	ES, S				
Single pump failure Double pump failure Loss of fluid DC power failure	, , ,	· · · · · · · · ·	I, I, I, I,	3.3.3.	16 17 18 19
OXYGEN					
Regulator indicator fai	lure		I.	12.	33
Regulator failure			I.	12.	34
Use of emergency oxyg	gen		I,	12,	36
PRESSURISATION MALFUNCTIONING			I,	11,	20
RADIO BAY COOLING	7				
MALFUNCTIONING			I,	11, 2	1 and 22
RELIGHTING	•••	<b>XXX</b>	III,	4,	8
SINGLE-ENGINE FLIG	HT		III,	4,	1 to 9

## 2 Considerations when abandoning

(a) Airborne ejection is the only proven means of abandoning the aircraft. The information given in the Flight Reference Cards concerning crash landings and ditching is for guidance only and may be invalidated by the particular circumstances. In any emergency involving escape from the aircraft, airborne ejection must be the first consideration.

(b) Although the ejection seats have a ground-level capability the minimum height for safe ejection varies, depending on speed and attitude. Under the worst conditions, several thousand feet are required for a successful ejection.

(c) Normally the canopy should be jettisoned before ejection and after speed has been reduced to 230 knots. If it is jettisoned above this speed, intercomm. becomes increasingly difficult, considerable amounts of dirt may be sucked up from the cockpit floor and buffeting may necessitate use of the seat-pan firing handle. Before ejecting, it must be clearly understood by both aircrew whether or not the canopy is to be jettisoned.

#### RESTRICTED

(d) If ejection through the canopy is necessary it is essential to adopt an upright sitting position and to concentrate on forcing the head back, throughout the ejection.

(e) If a situation arises which will ultimately necessitate ejection the procedure outlined in the Flight Reference Cards for "controlled ejection" ensures a safe ejection for the aircrew and that the aircraft crashes into a selected area. If the seat fails to eject after attempts have been made with both handles, a manual bale-out will have to be made. As the emergency oxygen bottle is secured to the seat, no oxygen supply will be available after a manual bale-out.

### 3 Considerations when using airfield arrester barrier

(a) Damage to external fuel tanks may occur on engagement. As this may result in fuel being spilt on hot brakes, external tanks should be emptied or jettisoned before entry.

(b) The canopy must be retained and closed to assist the top wire to pass over the cockpit.

(c) Heads must be ducked forward in case the wire penetrates the cockpits.

H



